

mAntra

TÉCNICO



MANTRA EN EL MUNDO

MANTRA AROUND THE WORLD







David Villalba

EN\_

Mantra works with a very diverse team of freelance designers, specialized in different branches of design.

They are a group of highly qualified professionals experience in the lighting sector, who contribute with original solutions in the development of new concepts; they also participate actively in the whole product development process, from the initial draft to the lasted finishing details

This wide variety of styles that our designers offer have a direct impact on our catalogues, which are made up of ideas that are adapted to any type of lighting need.

Besides, we take pride in having a great relationship with them, which goes beyond the professional link. We truly rely on their capability and work methods, which have provided, such innovative and stylish collections so far.

FR\_

Mantra collabore avec une équipe de dessinateurs externes très diverse, spécialisés dans différentes branches dans le monde du design.

Des professionnels avec une grande expérience dans le secteur de l'illumination, qui apportent des solutions innovatrices au développement de nouveaux concepts, et participent dans tous les processus de fabrication du produit, depuis le brouillon jusqu'à la conception du produit final.

Cette grande variété de styles influence directement notre catalogue, qui est composé de solutions qui s'adaptent à tous les styles ou besoins dans le monde de l'illumination.

Notre relation avec l'équipe de designers va plus loin que le contact professionnel, nous avons confiance sur leur savoir-faire, et leur méthodes de travail qui nous apporte fraîcheur et innovation, pour chacune de nos collections.



José Ignacio Ballester

JW design



Carlos Santolaria



Wilfried Buelacher



Jackie Luo



Santiago Sevillano

ITL\_

Mantra collabora con un team di designer esterni molto diversi, specializzati in varie branche nel mondo del design.

Professionisti con esperienza nel settore dell'illuminazione che forniscono soluzioni innovative nello sviluppo di nuovi concetti, partecipando a tutti i processi di sviluppo del prodotto, dallo schizzo iniziale alla concezione del prodotto finale.

Questa ampia varietà di stili che ci offre influisce direttamente sul nostro catalogo, che è composto da soluzioni che si adattano a qualsiasi tipo di stile o esigenza nel mondo dell'illuminazione.

Il nostro trattamento con i designer va oltre un semplice trattamento professionale, confidiamo pienamente nel loro buon lavoro e nei loro metodi di lavoro che ci danno freschezza e innovazione in ciascuna delle nostre collezioni.



Hugo Tejada

ESP\_

Mantra colabora con un equipo de diseñadores externos muy diverso, especializados en diversas ramas dentro del mundo del diseño.

Profesionales con experiencia en el sector de la iluminación que aportan soluciones novedosas en el desarrollo de nuevos conceptos, participando en todos los procesos de desarrollo del producto, desde el boceto inicial hasta la concepción del producto final.

Esta gran variedad de estilos que nos ofrecen incide directamente en nuestro catálogo, el cual está compuesto por soluciones que se adaptan a cualquier tipo de estilo o necesidad dentro del mundo de la iluminación.








Nuestro trato con los diseñadores va más allá de un mero trato profesional, confiamos plenamente en su buen hacer y en sus métodos de trabajo que nos aporta frescura e innovación en cada una de nuestras colecciones.
















INTERIOR/INDOOR







Aplique/Wall light

New						
						
ALTEA	ASIMETRIC	BOAVISTA	BORA BORA	BORACAY	CABARETE	CAICOS
20	56	78	88	198	76	86

New			New			
						
CAYMAN	COOK	DURBAN	ERIS	EYES	FUERTEVENTURA	FUJI
74	110	50	42	36	64	14







						
GOA	GOCOVA	HANOK	IOS	JERI	KUBICK	LANZAROTE
34	80	24	184	102	30	106

New		New				
						
LUPPI	MORNE	MURAL	ORION	PARACURU	PETACA	POLAR
28	54	94	16	100	108	48




New					
					
PREA	SAL	TAHITI	TAHITI XL	TARIFA	TENERIFE
84	70	96	18	82	104

INTERIOR/INDOOR

Aplique/Wall light








New			New		
					
TOBAGO	TOJA	TORCH	VENUS	VENUS	ZANZIBAR
22	98	66	38	40	58


Plafón/Ceiling

New		New				
						
BORA BORA	HANOK	KUBICK	MURAL	SAL	SAONA SUPERFICIE	TORCH
88	112	30	118	114	122	116


ZERO E27
120

Colgante/Pendant

New		New				
						
ARUBA	BASE COLGANTES	HANOK	IOS	ORION	PAGODA	SIRIO
160	162	128	126	140	136	150


TORCH
158



INTERIOR/INDOOR

Sobremesa/Table lamp

				
EYES	MURAL	SAL	TORCH	ZANZIBAR
166	170	164	168	172

Pie de salón/Floor lamp

			
EYES	MURAL	SAL	TORCH
176	180	174	178

Foco Superficie/Spotlight

						
ARUBA	BORACAY	COLUMBRETES	GLACIAR	GOWER	IOS	KAILUA
190	198	194	182	188	184	196


SAL
186

INTERIOR/INDOOR

Foco carril trifásico/Triphasic rail spot

					
ARUBA	CARRILES-TRACKS	FIJI	ÍPSILON	PAGODA	SAL
208	218	212	200	204	210

Empotrable/Recessed

						
ATLANTIS	BÁSICO GU10	BRANDON	CABRERA	CIES	COMFORT IP	COMFORT GU10
258	244	250	234	256	269	248

New

						
FORMENTERA	GARDA	GUINCHO	GUINCHO GU10	GRACIOSA	LAMBORJINI	MEDANO
230	226	222	224	242	259	236

New

		
METACRILATO	NEPTUNO	SAONA
254	228	238

Campanas Led/Ufo bays Led

	
CAMPANAS	CAMPANAS
284	288

Tiras Led/Strip Leds


































			
DRIVERS	PERFILES	SISTEMAS	TIRAS LED
275	264	278	260

New



EXTERIOR/OUTDOOR

Aplique/Wall light





<div>New</div>						
			<div>New</div> 			
ALPINE 346	ANDES 292	ARCS 298	BERET 297	BORA 336	CHAMONIX 348	CERLER 357
<div>New</div>						
						
CYCLE 300	DAVOS 324	DAVOS XL 328	DAVOS DOUBLE 330	EVEREST 322	IGUAZÚ 316	JACKSON 354
<div>New</div>						
						
KANDANCHÚ 320	LEVI 352	LOTUS 294	MAYA 304	MERIBEL 308	MERIBEL 340	POLINESIA 302
						
RODAS 356	RUKA 306	SOCHI 334	SOLDEN 344	TAOS 350	TEJA 312	TIGNES 357
						
TRIAx 332	UTAH 338	VERBIER 364	VOLCANO 314	YETI 342		

EXTERIOR/OUTDOOR

Plafón exterior/Ceiling outdoor

<div>New</div>						
						<div>New</div> 
BACHELOR 368	CHAMONIX 366	KANDANCHÚ 358	LEVI 370	MAYA 362	VERBIER 364	VOLCANO 360

Colgantes exterior/Pendant outdoor

			
AVORIAZ 384	KINKÉ 376	MAYA 382	POLINESIA 372



EXTERIOR/OUTDOOR


Sobremesa exterior portátil/Portable outdoor table lamp

	New	New	New	New	
					
K2	K3	K4	K5	RELAX	RELAX
396	394	392	390	388	386

Lámpara de suelo exterior portátil/Portable outdoor floor lamp











			
ASTÚN	FLAME	K2	SAPORO
402	404	398	400

Sobremuro exterior/Over wall lamp

			
MAYA	MERIBEL	MERIBEL	RUKA
410	406	408	412

EXTERIOR/OUTDOOR

Balizas-Piquetas-Lámparas de suelo/Bollards-spike-ground lamps

New			New			New
						
ALPINE	AVORIAZ	CHEVALIER	CHICAGO	ESPIGA	FLAME	QUEBEC
416	428	414	418	430	432	424
						
RUKA	TAOS	TAOS	TIGNES			
412	420	426	422			

Bañadores/Step lights

	
ASPEN	BAKER
438	434

Accesorios/Accessories

		
CONEXIÓN IP68	PIQUETAS	DISCO
442	443	443

BOMBILLAS/BULB

Bombillas/Bulb

	New		New		
					
G9	G4	GU10	E14	E27	GX53
444	446	447	451	454	465

# FUJI


by José Ignacio Ballester

Apliques-Wall lights


Indoor



14W



10W



	REFERENCE	K	LED WATT	LUMENS	FINISH
New	8156	3000K	10W	920lm	Blanco-White
New	8157	3000K	10W	920lm	Negro-Black
New	8158	3000K	14W	1250lm	Blanco-White
New	8159	3000K	14W	1250lm	Negro-Black
220-240V ~ 50/60Hz CRI:≥ 80					Metal-Metal






ORION  
by Hugo Tejada


Appliques - Wall lights

Indoor




REFERENCE	K	LED WATT	LUMENS	FINISH	SIZES
New 8122	3000K	8W	560lm	Negro+blanco-Black+white	ø250
New 8123	3000K	8W	560lm	Negro+Madera-Black+Wood	ø250
New 8124	3000K	8W	560lm	Negro+Pan oro-Black+Gold leaf	ø250
New 8125	3000K	20W	1400lm	Negro+blanco-Black+white	ø400
New 8126	3000K	20W	1400lm	Negro+Madera-Black+Wood	ø400
New 8127	3000K	20W	1400lm	Negro+Pan oro-Black+Gold leaf	ø400
New 8128	3000K	24W	1680lm	Negro+blanco-Black+white	ø500
New 8129	3000K	24W	1680lm	Negro+Madera-Black+Wood	ø500
New 8130	3000K	24W	1680lm	Negro+Pan oro-Black+Gold leaf	ø500

220-240V~ 50/60Hz CRI ≥80      Hierro/Acrílico-Iron/Acrylic









REFERENCE		K	LED WATT	LUMENS	FINISH
New	8089	3000K	12W	1080lm	Blanco-White
New	8090	3000K	12W	1080lm	Negro-Black
New	8087	3000K	36W	3240lm	Blanco-White
New	8088	3000K	36W	3240lm	Negro-Black
			220-240V~ 50/60Hz CRI:≥ 80		Aluminio/Acrílico- Aluminium/Acrylic








	REFERENCE	K	LED WATT	LUMENS	FINISH
New	8094	3000K	15W	1200lm	Blanco arena-Sand white
New	8098	4000K	15W	1275lm	Blanco arena-Sand white
New	8093	3000K	21W	1680lm	Blanco arena-Sand white
New	8097	4000K	21W	1785lm	Blanco arena-Sand white
New	8092	3000K	30W	2400lm	Blanco arena-Sand white
New	8096	4000K	30W	2550lm	Blanco arena-Sand white
New	8091	3000K	40W	3200lm	Blanco arena-Sand white
New	8095	4000K	40W	3400lm	Blanco arena-Sand white
220-240V~ 50/60Hz CRI:≥ 80					Aluminio/Acrílico-Aluminium/Acrylic









	REFERENCE	K	LED WATT	LUMENS	FINISH
New	7910	3000K	7W	590lm	Blanco-White
New	7913	3000K	7W	590lm	Negro-Black
New	7911	3000K	9W	760lm	Blanco-White
New	7914	3000K	9W	760lm	Negro-Black
New	7912	3000K	12W	1010lm	Blanco-White
New	7915	3000K	12W	1010lm	Negro-Black
220-240V~ 50/60Hz CRI:≥ 90					Aluminio-Aluminium






REFERENCE	K	LED WATT	LUMENS	FINISH
7774	3000K	14W	950lm	Blanco-White
7776	3000K	14W	950lm	Negro-Black
7778	3000K	14W	950lm	Arena-Sabbia
7775	4000K	14W	1000lm	Blanco-White
7777	4000K	14W	1000lm	Negro-Black
220-240V~50/60Hz CRI:≥ 80				Aluminio-Aluminium










REFERENCE	K	LED WATT	LUMENS	FINISH
7770	3000K	38 W	2850lm	Blanco-White
7772	3000K	38 W	2850lm	Negro-Black
7771	4000K	38 W	3000lm	Blanco-White
7773	4000K	38 W	3000lm	Negro-Black
220-240V~50/60Hz CR! ≥ 80				Aluminio-Aluminium








REFERENCE	BULB (No incl)	FINISH
7693	1L x GX53	Blanco-White
7694	1L x GX53	Negro-Black
7695	1L x GX53	Arena-Sabbia
máx. 15W LED (No incl)		100-240V~50/60Hz Metal-Metal



Bombillas recomendadas-Suggested bulbs

REFERENCE	Wattios LED	K	Lumens	Ángulo luz
R09224	9 W	3000K	730lm	120°
R09225	9 W	4000K	740lm	120°
R09248	12W	3000K	930lm	120°
R09249	12W	4000K	960lm	120°





REFERENCE	K	LED WATT	LUMENS	FINISH	
7590	3000K	12W +14W	1630lm	Blanco mate-Matt white	On-off
7592	3000K	12W +14W	1630lm	Negro mate-Matt black	On-off
7591	3000K	12W +14W	1630lm	Blanco mate-Matt white	Dimmable
7593	3000K	12W +14W	1630lm	Negro mate-Matt black	Dimmable
7594	3000K	13,5W + 20W	1870lm	Blanco mate-Matt white	On-off
7596	3000K	13,5W + 20W	1870lm	Negro mate-Matt black	On-off
7595	3000K	13,5W + 20W	1870lm	Blanco mate-Matt white	Dimmable
7597	3000K	13,5W + 20W	1870lm	Negro mate-Matt black	Dimmable
7760	3000K	18W+30W	2700lm	Blanco mate-Matt white	On-off
7762	3000K	18W+30W	2700lm	Negro mate-Matt black	On-off
7761	3000K	18W+30W	2700lm	Blanco mate-Matt white	Dimmable
7763	3000K	18W+30W	2700lm	Negro mate-Matt black	Dimmable
220-240V~50/60Hz CRI:≥ 80				Aluminio-Aluminium	









KUBICK

by José Ignacio Ballester

Apliques - Wall lights



Indoor






GOA  
by José Ignacio Ballester

Apliques-Wall lights


Indoor



REFERENCE	K	LED WATT	LUMENS	FINISH	
7720	3000K	7.5W	660lm	Blanco mate-Matt white	Con interruptor With switch
7721	3000K	7.5W	660lm	Negro mate-Matt black	Con interruptor With switch
220-240V~50/60Hz CRI:≥ 80				Aluminio-Aluminium	







REFERENCE	K	LED WATT	LUMENS	FINISH	
7513	3000K	6W	390lm	Negro arena-Sand black	Sin interruptor No switch
7514	3000K	6W	390lm	Negro arena-Sand black	Con interruptor With switch
220-240V~50/60Hz CRI:≥ 80				Aluminio-Aluminium	



7512  
pág. 176



7510  
pág. 166






VENUS  
by Hugo Tejada


Apliques - Wall lights

Indoor



	REFERENCE	K	LED WATT	LUMENS	FINISH	SIZES
New	8010	3000K	9W	780lm	Blanco-White	Ø225
New	8011	3000K	9W	780lm	Negro-Black	Ø225
New	8034	3000K	9W	780lm	Oro-Gold	Ø225
New	8012	3000K	18W	1440lm	Blanco-White	Ø500
New	8013	3000K	18W	1440lm	Negro-Black	Ø500
New	8035	3000K	18W	1440lm	Oro-Gold	Ø500
			220-240V ~ 50/60Hz CRI≥ 80		Aluminio/Acrílico-Aluminum/Acrylic	

Registered N°007663331-0016









VENUS  
by Hugo Tejada

Aplique/Perchero-Wall light/Coat Rack

Indoor



REFERENCE	K	LED WATT	LUMENS	FINISH
7293	3000K	6 W	490lm	Negro-Black
7292	3000K	6 W	490lm	Blanco-White
			220-240V~50/60Hz CRI≥ 80	Aluminio/acrílico-Aluminium/acrylic
Registered N°007663331-0016				




DRIVER  
TUV

Registered N°007663331-00160016


ERIS

by Hugo Tejada



REFERENCE	K	LED WATT	LUMENS	FINISH
7296	3000K	8W	640lm	Blanco-White
7297	3000K	8W	640lm	Negro-Black
220-240V~50/60Hz CRI≥ 80				Aluminio-Aluminium

Registered N°007663331-0012



DRIVER  
TUV


Registered N°007663331-0012





ERIS  
by Hugo Tejada

Apliques - Wall lights

Indoor



REFERENCE	K	LED WATT	LUMENS	FINISH
7298	3000K	16W	1280lm	Blanco-White
7299	3000K	16W	1280lm	Negro-Black
220-240V ~50/60Hz CRI≥ 80				Aluminio-Aluminium




DRIVER  
TUV

Registered N°007663331-0012

ERIS  
by Hugo Tejada



REFERENCE	K	LED WATT	LUMENS	FINISH
7300	3000K	24W	1920lm	Blanco-White
7301	3000K	24W	1920lm	Negro-Black
220-240V ~50/60Hz CRI≥ 80				Aluminio-Aluminium



DRIVER  
TÜV

Registered N°007663331-0012




POLAR  
by Hugo Tejada

Aplique/Perchero-Wall light/Coat Rack

Indoor



REFERENCE	K	LED WATT	LUMENS	FINISH
7240	3000K	6W	540lm	Blanco-White
7241	3000K	6W	540lm	Negro-Black
220-240V~50/60Hz CRI≥ 80				Aluminio-Aluminium




DRIVER  
TUV

Registered N° 007663331-0015




REFERENCE	K	LED WATT	LUMENS	FINISH
7175	3000K	10W	780lm	Negro-Black
7176	3000K	20W	1550lm	Negro-Black
7177	3000K	30W	2300lm	Negro-Black
220-240V ~50/60Hz CRI≥ 80				Aluminio-Aluminium








REFERENCE	K	LED WATT	LUMENS	FINISH
7197	3000K	10W	780lm	Blanco-White
7198	3000K	20W	1550lm	Blanco-White
7199	3000K	30W	2300lm	Blanco-White
220-240V~50/60Hz CRI≥ 80				Aluminio-Aluminium





REFERENCE	K	LED WATT	LUMENS	FINISH
7482	4000K	12W	1080lm	Negro-Black
6760	4000K	12W	1080lm	Cromo-Chrome
6763	4000K	12W	1080lm	Blanco-White
7483	4000K	16W	1440lm	Negro-Black
6761	4000K	16W	1440lm	Cromo-Chrome
7480	4000K	16W	1440lm	Blanco-White
7484	4000K	20W	1800lm	Negro-Black
6762	4000K	20W	1800lm	Cromo-Chrome
7481	4000K	20W	1800lm	Blanco-White
220-240V ~50/60Hz CRI≥ 80				Aluminio/Pc-Aluminium







ASIMETRIC  
by Santolaria & Lluscà

Apliques-Wall lights


Indoor







REFERENCE	BULB (No incl)	FINISH
6220	1L x GX53	Blanco-White
6221	1L x GX53	Blanco-White
6222	1L x GX53	Negro-Black
máx. 12W LED (No incl)		100-240V~50/60Hz Metal-Metal



Registered N° 004721413-026




Bombillas recomendadas-Suggested bulbs



REFERENCE	Wattios LED	CCT	Lumens	Ángulo luz
 R09224	9W	3000K	730lm	120°
 R09225	9W	4000K	740lm	120°
 R09248	12W	3000K	930lm	120°
 R09249	12W	4000K	960lm	120°



6221




6220





REFERENCE	K	LED WATT	LUMENS	FINISH
6750	3000K	3W	210lm	Blanco arena-Sand white
6752	3000K	3W	210lm	Negro arena-Sand black
100-240V~50/60Hz CRI≥ 80				Aluminio/Metal-Aluminium/Metal

 \*Cargador Inalámbrico de inducción-Wireless Induction Charger








REFERENCE	K	LED WATT	LUMENS	FINISH
6754	3000K	3W	210lm	Blanco mate-Matt white
6755	3000K	3W	210lm	Negro mate-Matt black
100-240V~50/60Hz CRI≥ 80				Aluminio/Metal-Aluminium/Metal




\*Cargador Inalámbrico de inducción-Wireless Induction Charger





REFERENCE	K	LED WATT	LUMENS	FINISH
6751	3000K	6W	470lm	Blanco mate-Matt white
6753	3000K	6W	470lm	Negro mate-Matt black
		220-240V~50/60Hz CRI≥ 80		Aluminio/Metal-Aluminium/Metal


 \*Cargador Inalámbrico de inducción-Wireless Induction Charger









REFERENCE	K	LED WATT	LUMENS	FINISH
6865	3000K	9W	600lm	Blanco mate-Matt white
6866	3000K	9W	600lm	Negro mate-Matt black
100-250V~ 50/60Hz CRI:≥ 80			Acero/Acrílico-Steel/Acrylic	






REFERENCE	K	LED WATT	LUMENS	FINISH
6700	3000K	6 W	410lm	Blanco mate-Matt white
6701	3000K	6 W	410lm	Negro mate-Matt black
220-240V~50/60Hz CRI≥ 80				Aluminio-Aluminium







REFERENCE	K	LED WATT	LUMENS	FINISH
6702	3000K	6W+3W	410lm+210lm	Blanco mate-Matt white
6703	3000K	6W+3W	410lm+210lm	Negro mate-Matt black
220-240V~50/60Hz CRI≥ 80				Aluminio-Aluminium





REFERENCE	BULB (No incl)	FINISH	
7523	1L x GU10	Blanco mate-Matt white	Sin interruptor No switch
7518	1L x GU10	Negro mate-Matt black	Sin interruptor No switch
7524	1L x GU10	Blanco mate-Matt white	Con interruptor With switch
7519	1L x GU10	Negro mate-Matt black	Con interruptor With switch
máx. 10W LED (No incl)		100-240V~50/60Hz Aluminio-Aluminium	

Bombillas recomendadas-Suggested bulbs				
K	Wat LED	On/Off	Dimmable	Lumens
2700K	7W	R09254	R09257	510lm
3000K	7W	R09255	R09258	540lm
4000K	7W	R09256	R09259	570lm

ON/OFF  
Incl.

2 años  
WARRANTY  
GARANTIA

NOT INCLUDED

IP20




ErP  
COMPLIANT

RoHS  
compliant







REFERENCE	BULB (No incl)	FINISH	
6283	1L x GU10	Blanco mate-Matt white	Sin interruptor No switch
6713	1L x GU10	Negro mate-Matt black	Sin interruptor No switch
6284	1L x GU10	Blanco mate-Matt white	Con interruptor With switch
6714	1L x GU10	Negro mate-Matt black	Con interruptor With switch
máx. 10W LED (No incl)		100-240V~50/60Hz Aluminio-Aluminium	

Bombillas recomendadas-Suggested bulbs				
K	Wat LED	On/Off	Dimmable	Lumens
2700K	7W	R09254	R09257	510lm
3000K	7W	R09255	R09258	540lm
4000K	7W	R09256	R09259	570lm

ON/OFF  
Incl.

garantía manifiesto 2 años WARRANTY 2 YEARS


NOT INCLUDED

IP20



ErP  
COMPLIANT

RoHS  
compliant





REFERENCE	K	LED WATT	LUMENS	FINISH
6080	3000K	3+6 W	210+410lm	Blanco mate-Matt white
6081	3000K	3+6 W	210+410lm	Níquel satinado-Satin nickel
6082	3000K	3+6 W	210+410lm	Cuero-Antique brass
6083	3000K	3+6 W	210+410lm	Negro mate-Matt black
New 7853	3000K	3+6 W	210+410lm	Oro-Gold
220-240V~ 50/60Hz CRI:≥ 80				Aluminio-Aluminium



REFERENCE	K	LED WATT	LUMENS	FINISH
New 7823	3000K	3+6 W	210+410lm	Blanco mate-Matt white
New 7824	3000K	3+6 W	210+410lm	Níquel satinado-Satin nickel
New 7825	3000K	3+6 W	210+410lm	Cuero-Antique brass
New 7826	3000K	3+6 W	210+410lm	Negro mate-Matt black
New 7854	3000K	3+6 W	210+410lm	Oro-Gold
220-240V~ 50/60Hz CRI:≥ 80				Aluminio-Aluminium






CABARETE

Apliques - Wall lights

Indoor

REFERENCE	K	LED WATT	LUMENS	FINISH
5715	3000K	3+3W	470lm	Blanco mate-Matt white
		220-240V~ 50/60Hz CRI≥ 80		Aluminio-Aluminium



REFERENCE	K	LED WATT	LUMENS	FINISH
5714	3000K	3+3W	470lm	Negro mate-Matt black
		220-240V~ 50/60Hz CRI≥ 80		Aluminio-Aluminium



DRIVER  
TUV

ON/OFF  
Incl.

LED life / LED vida  
30.000 h

ON / OFF  
30.000

garantía mantraco 5 años  
WARRANTY 5  
GARANTIA 5  
LED

LED  
INCLUDED

IP20

ErP  
COMPLIANT

RoHS  
compliant






REFERENCE	K	LED WATT	LUMENS	FINISH
6046	3000K	3W	185lm	Blanco-White
6047	3000K	3W	185lm	Negro-Black
220-240V ~ 50/60Hz CRI: ≥ 80				Aluminio/acrílico - Aluminium/acrylic



REFERENCE	K	LED WATT	LUMENS	FINISH
6050	3000K	5W	285lm	Blanco-White
6051	3000K	5W	285lm	Negro-Black
220-240V ~ 50/60Hz CRI: ≥ 80				Aluminio - Aluminium




REFERENCE	K	LED WATT	LUMENS	FINISH
6048	3000K	3W	185lm	Blanco-White
6049	3000K	3W	185lm	Negro-Black
220-240V ~ 50/60Hz CRI: ≥ 80				Aluminio - Aluminium








REFERENCE	K	LED WATT	LUMENS	FINISH
6820	3000K	3W	210lm	Blanco arena-Sand white
6821	3000K	3W	210lm	Negro arena-Sand black
100-240V~50/60Hz CRI≥ 80				Aluminio-Aluminium









REFERENCE	K	LED WATT	LUMENS	FINISH
6070	3000K	3W	210lm	Blanco mate-Matt white
6071	3000K	3W	210lm	Níquel satinado-Satin nickel
6072	3000K	3W	210lm	Cuero-Antique brass
100-240V-50/60Hz CRI:≥ 80				Aluminio-Aluminium







REFERENCE	K	LED WATT	LUMENS	FINISH
6075	3000K	3W	210lm	Blanco mate - Matt white
6076	3000K	3W	210lm	Níquel satinado - Satin nickel
6077	3000K	3W	210lm	Cuero - Antique brass
100-240V - 50/60Hz CRI: ≥ 80				Aluminio - Aluminium












REFERENCE	BULB (No incl)	FINISH	LECTOR/READER	LUMENS
6091	1L x E27	Blanco mate-Matt white	3W	210lm
6092	1L x E27	Níquel Satinado-Satin Nickel	3W	210lm
6093	1L x E27	Cuero-Antique brass	3W	210lm
máx. 20W LED (No incl)		220-240V~50/60Hz CRI:≥ 80 Aluminio-Aluminium	Cargador USB /Charger USB Pantalla blanca/White shade	


USB  
Output







REFERENCE	K	LED WATT	LUMENS	FINISH
C0127	2700K	6W	420lm	Blanco-White
C0131	2700K	6W	420lm	Negro-Black
C0101	3000K	6W	540lm	Blanco-White
C0111	3000K	6W	540lm	Plata-Silver
C0119	3000K	6W	540lm	Negro-Black
C0128	2700K	12W	840lm	Blanco-White
C0132	2700K	12W	840lm	Negro-Black
C0102	3000K	12W	1080lm	Blanco-White
C0112	3000K	12W	1080lm	Plata-Silver
C0120	3000K	12W	1080lm	Negro-Black
220-240V-50/60Hz CRI:≥ 80				Aluminio-Aluminium







BORA BORA

Apliques - Wall lights


Indoor



REFERENCE	K	LED WATT	LUMENS	FINISH
C0129	2700K	16 W	1120lm	Blanco-White
C0133	2700K	16 W	1120lm	Negro-Black
C0117	3000K	16 W	1350lm	Blanco-White
C0118	3000K	16 W	1350lm	Plata-Silver
C0124	3000K	16 W	1350lm	Negro-Black
C0130	2700K	30 W	2100lm	Blanco-White
C0134	2700K	30 W	2100lm	Negro-Black
C0125	3000K	30 W	2400lm	Blanco-White
C0126	3000K	30 W	2400lm	Negro-Black
220-240V~50/60Hz CRI:≥ 80				Aluminio-Aluminium








C0103-C0113

C0104-C0114

C0115


C0116






REFERENCE	K	LED WATT	LUMENS	FINISH	SIZES
C0103	3000K	6 W	540lm	Blanco-White	130 × 130
C0113	3000K	6 W	540lm	Plata-Silver	130 × 130
C0115	3000K	6 W	540lm	Plata-Silver	144 × 135
C0104	3000K	12W	1080lm	Blanco-White	180 × 180
C0114	3000K	12W	1080lm	Plata-Silver	180 × 180
C0116	3000K	12W	1080lm	Plata-Silver	192 × 180
220-240V ~50/60Hz CRI:≥ 80				Aluminio-Aluminium	







REFERENCE	K	LED WATT	LUMENS	FINISH	INPUT	
6230	3000K	24W	1440lm	Blanco mate-Matt white	100-250V~ 50/60Hz	On-off
7460	3000K	24W	1440lm	Negro mate-Matt black	100-250V~ 50/60Hz	On-off
New 7840	3000K	24W	1440lm	Blanco mate-Matt white	220-240V~50/60Hz	Dimmable 
New 7841	3000K	24W	1440lm	Negro mate-Matt black	220-240V~50/60Hz	Dimmable 
					CRI: ≥ 80	Aluminio-Aluminium



6563  
pág. 180



6562  
pág. 170



6560  
pág. 118









REFERENCE	K	LED WATT	LUMENS	FINISH
C0089	3000K	6W	215lm	Blanco mate - Matt white
		220-240V~50/60Hz CRI:≥ 80	Aluminio - Aluminium	







REFERENCE	K	LED WATT	LUMENS	FINISH
6253	3000K	8 W	720lm	Blanco- White
5120	4000K	8 W	720lm	Blanco- White
6254	3000K	16 W	1410lm	Blanco- White
5121	4000K	16 W	1410lm	Blanco- White
220-240V~50/60Hz CRI:≥ 80				Aluminio- Aluminium









REFERENCE	K	LED WATT	LUMENS	FINISH
6382	3000K	8W	619lm	Cuero-Antique brass
6380	3000K	8W	619lm	Cromo-Chrome
6383	3000K	12W	908lm	Cuero-Antique brass
6381	3000K	12W	908lm	Cromo-Chrome
6385	3000K	18W	1257lm	Cuero-Antique brass
6384	3000K	18W	1257lm	Cromo-Chrome
175-265V - 50/60Hz CRI:≥ 80				Aluminio-Aluminium






REFERENCE	K	LED WATT	LUMENS	FINISH
6370	3000K	8 W	421lm	Cromo-Chrome
6374	3000K	24 W	1497lm	Cromo-Chrome
175-265V~50/60Hz CRI:≥ 80				Aluminio-Aluminium









REFERENCE	K	LED WATT	LUMENS	FINISH
6870	3000K	8 W	640lm	Blanco-White
6871	4000K	8 W	680lm	Blanco-White
+USB		100-250V~ 50/60Hz CRI:≥ 80	Acero/Silicona-Steel/Silicon	






REFERENCE	K	LED WATT	LUMENS	FINISH
6875	3000K	18W	1400lm	Blanco-White
6876	3000K	18W	1400lm	Negro-Black
+USB x 2		220-240V~ 50/60Hz CRI:≥ 80	Aluminio-Aluminium	







REFERENCE	K	LED WATT	LUMENS	FINISH
6043	3000K	16 W	1350lm	Blanco mate-Matt white
		220-240V~50/60Hz CRI:≥ 80		Aluminio-Aluminium








7111




7110



REFERENCE	K	LED WATT	LUMENS	FINISH
7110	3000K	10W	780lm	Blanco-White
7111	3000K	12,5W	975lm	Blanco-White
220-240V~ 50/60Hz CRI:≥ 80				Yeso-Gypsum







REFERENCE	K	LED WATT	LUMENS	FINISH
7949	3000K	14W	950lm	Blanco-White
7951	3000K	14W	950lm	Negro-Black
7953	3000K	14W	950lm	Arena-Sabbia
7950	4000K	14W	1000lm	Blanco-White
7952	4000K	14W	1000lm	Negro-Black
7945	3000K	38W	2850lm	Blanco-White
7947	3000K	38W	2850lm	Negro-Black
7946	4000K	38W	3000lm	Blanco-White
7948	4000K	38W	3000lm	Negro-Black
220-240V~50/60Hz CRI≥ 80				Aluminio-Aluminium


7548  
pág. 132

7953  
pág. 24


7546  
pág. 128







REFERENCE	BULB (No incl)	FINISH
7961	3L x GU10	Blanco mate-Matt white
7962	3L x GU10	Negro mate-Matt black
máx. 10W LED (No incl) 100-240V~50/60Hz Aluminio-Aluminium		




Bombillas recomendadas-Suggested bulbs

K	Wat LED	On/Off	Dimmable	Lumens
2700K	7W	R09254	R09257	510lm
3000K	7W	R09255	R09258	540lm
4000K	7W	R09256	R09259	570lm







360°



REFERENCE	K	LED WATT	LUMENS	FINISH
6827	3000K	36 W	2850lm	Blanco arena-Sand white
6828	3000K	36 W	2850lm	Negro arena-Sand black
220-240V-50/60Hz CRI:≥ 80				Aluminio-Aluminium




360°







REFERENCE	K	LED WATT	LUMENS	FINISH	
6560	3000K	48W	3840lm	Blanco mate-Matt white	On-off
6561	3000K	48W	3840lm	Blanco mate-Matt white	Dimmable 
7462	3000K	48W	3840lm	Negro-Black	On-off
7463	3000K	48W	3840lm	Negro-Black	Dimmable 
		220-240V~50/60Hz CRI:≥ 80		Aluminio- Aluminium	



6230  
pág. 94



6563  
pág. 180





6562  
pág.170








REFERENCE	BULB NO INCLUDED	FINISH
5410	5L x E27	Blanco-White
5411	3L x E27	Blanco-White
máx. 20W LED (No incl) 100-240V~50/60Hz Metal-Metal/Acrylic		






Downlight en superficie para paredes y soluciones sin falso techo.

REFERENCE	K	LED WATT	LUMENS	FINISH
6620	3000K	8W	680lm	Blanco mate-Matt white
6621	4000K	8W	720lm	Blanco mate-Matt white
6622	3000K	14W	1190lm	Blanco mate-Matt white
6623	4000K	14W	1260lm	Blanco mate-Matt white
6624	3000K	24W	2040lm	Blanco mate-Matt white
6625	4000K	24W	2160lm	Blanco mate-Matt white
6626	3000K	30W	2550lm	Blanco mate-Matt white
6627	4000K	30W	2700lm	Blanco mate-Matt white
220-240V~50/60Hz CRI≥ 80				Aluminio-Aluminium









Downlight en superficie para paredes y soluciones sin falso techo.

REFERENCE	K	LED WATT	LUMENS	FINISH
6628	3000K	8W	680lm	Blanco mate-Matt white
6629	4000K	8W	720lm	Blanco mate-Matt white
6630	3000K	14W	1190lm	Blanco mate-Matt white
6631	4000K	14W	1260lm	Blanco mate-Matt white
6632	3000K	24W	2040lm	Blanco mate-Matt white
6633	4000K	24W	2160lm	Blanco mate-Matt white
6634	3000K	30W	2550lm	Blanco mate-Matt white
6635	4000K	30W	2700lm	Blanco mate-Matt white
220-240V~50/60Hz CRI≥ 80				Aluminio-Aluminium










REFERENCE	BULB (No incl)	FINISH
7936	6L x GU10	Blanco-White
7937	6L x GU10	Negro-Black
máx. 12W LED (No incl)		100-240V~50/60Hz Aluminio-Aluminium



7595  
pág. 184



Bombillas recomendadas-Suggested bulbs				
K	Wat LED	On/Off	Dimmable	Lumens
 2700K	7W	R09254	R09257	510lm
 3000K	7W	R09255	R09258	540lm
 4000K	7W	R09256	R09259	570lm








HANOK  
by David Villalba

Lámpara lineal-Linear lamp

Indoor



REFERENCE	K	LED WATT	LUMENS	FINISH
7542	3000K	38 W	2850lm	Blanco-White
7546	3000K	38 W	2850lm	Negro-Black
7569	3000K	38 W	2850lm	Arena-Sabbia
7543	4000K	38 W	3000lm	Blanco-White
7547	4000K	38 W	3000lm	Negro-Black
On-off		220-240V~ 50/60Hz CRI≥ 80		Aluminio-Aluminium




HANOK  
by David Villalba

Lámpara lineal-Linear lamp


Indoor




REFERENCE	K	LED WATT	LUMENS	FINISH
7540	3000K	38W	2650lm	Blanco-White
7544	3000K	38W	2650lm	Negro-Black
7541	4000K	38W	2800lm	Blanco-White
7545	4000K	38W	2800lm	Negro-Black
UGR<16		220-240V~ 50/60Hz CRI≥ 90		Aluminio-Aluminium








REFERENCE	K	LED WATT	LUMENS	FINISH
7548	3000K	38 W	2650lm	Blanco- White
7549	4000K	38 W	2800lm	Blanco- White
UGR<16		220-240V~ 50/60Hz CRI≥ 80		Aluminio- Aluminium




REFERENCE	
7550	Tapa lateral con cable fijación-Side cover white with fixing wire
7551	Tapa lateral con cable alimentación y florón-Side cover white with ac wire & rosette
7552	Conexión intermedia con cable fijación-Middle connection white with fixing wire
7553	Conexión intermedia con cable alimentación y florón - Middle connection white with ac wire & rosette







REFERENCE	K	LED WATT	LUMENS	FINISH
7554	3000K	38W	2650lm	Negro-Black
7555	4000K	38W	2800lm	Negro-Black
	UGR<16	220-240V~ 50/60Hz CRI≥ 80		Aluminio-Aluminium



REFERENCE	
7556	Tapa lateral con cable fijación-Side cover white with fixing wire
7557	Tapa lateral con cable alimentación y florón-Side cover white with ac wire & rosette
7558	Conexión intermedia con cable fijación-Middle connection white with fixing wire
7559	Conexión intermedia con cable alimentación y florón - Middle connection white with ac wire & rosette






PAGODA  
by David Villalba

Colgante-Pendant lamp

Indoor  
UGR<16

CRI≥90



REFERENCE	K	LED WATT	LUMENS	FINISH
7784	3000K	12,5W	950lm	Blanco-White
7786	3000K	12,5W	950lm	Negro-Black
7785	4000K	12,5W	1050lm	Blanco-White
7787	4000K	12,5W	1050lm	Negro-Black
UGR<16		220-240V ~ 50/60Hz	CRI:≥ 90	Aluminio-Aluminium



7788  
pág. 204



# PAGODA



by David Villalba

Colgante-Pendant lamp

Indoor



REFERENCE	BULB (No incl)	FINISH
7790	1L x GU10	Blanco-White
7791	1L x GU10	Negro-Black
máx. 12W LED (No incl)		100-240V~50/60Hz Aluminio-Aluminium



Bombillas recomendadas-Suggested bulbs				
K	Wat LED	On/Off	Dimmable	Lumens
2700K	7W	R09254	R09257	510lm
3000K	7W	R09255	R09258	540lm
4000K	7W	R09256	R09259	570lm






ORION  
by Hugo Tejada

Lámpara de techo-Pendant lamp

Indoor

REFERENCE	K	LED WATT	LUMENS	FINISH
7475	3000K	24W	1770 lm	Negro/cuero-Black/antique brass
		220-240V ~ 50/60Hz CRI≥ 80	Aluminio/Acrílico-Aluminium/Acrylic	

8128  
pág. 16



DRIVER  
TUV

LED life / LED vida  
30.000 h

ON / OFF  
30.000

LED  
INCLUDED

5

garantía mantenido por  
WARRANTY  
GARANTIA  
LED

IP20





ORION  
by Hugo Tejada

Lámpara de techo-Pendant lamp

Indoor



REFERENCE	K	LED WATT	LUMENS	FINISH
7476	3000K	32W	2360lm	Negro/cuero-Black/antique brass
220-240V~ 50/60Hz CRI≥ 80				Aluminio/Acrílico-Aluminium/Acrylic



8128  
pág. 16

DRIVER  
TUV






ORION  
by Hugo Tejada

Lámparas de techo-Pendant lamp

Indoor



REFERENCE	K	LED WATT	LUMENS	FINISH
7305	3000K	8W	590lm	Negro/cuero-Black/antique brass
220-240V ~ 50/60Hz CRI≥ 80				Aluminio/Acrílico-Aluminium/Acrylic



ORION  
by Hugo Tejada


Lámparas de techo-Pendant lamp

Indoor



REFERENCE	K	LED WATT	LUMENS	FINISH
7306	3000K	16W	1180lm	Negro/cuero-Black/antique brass
	6 und	reference 7308	included	Blocacables-WireLocker
		220-240V ~ 50/60Hz CRI≥ 80		Aluminio/Acrílico-Aluminium/Acrylic

7308 Blocacables-WireLocker 1 und



DRIVER  
TÜV

Registered N° 007663331-0014



ORION  
by Hugo Tejada


Lámparas de techo-Pendant lamp

Indoor



REFERENCE	K	LED WATT	LUMENS	FINISH
7307	3000K	32W	2360lm	Negro/cuero-Black/antique brass
	12 und	reference 7308	included	Blocacables-WireLocker
		220-240V~ 50/60Hz CRI≥ 80		Aluminio/Acrílico-Aluminium/Acrylic

7308 Blocacables-WireLocker 1 und



Registered N° 007663331-0014



SIRIO  
by Hugo Tejada

Lámparas de techo-Pendant lamp

Indoor



REFERENCE	K	LED WATT	LUMENS	FINISH
7312	3000K	24W	1770lm	Negro-Black
220-240V~ 50/60Hz CRI≥ 80 Aluminio/Acrílico-Aluminium/Acrylic				







SIRIO  
by Hugo Tejada

Indoor

Lámparas de techo-Pendant lamp



REFERENCE	K	LED WATT	LUMENS	FINISH
7313	3000K	32W	2360lm	Negro-Black
220-240V~ 50/60Hz CRI≥ 80				Aluminio/Acrílico-Aluminium/Acrylic



SIRIO  
by Hugo Tejada

Lámparas de techo-Pendant lamp

Indoor



REFERENCE	K	LED WATT	LUMENS	FINISH
7310	3000K	8W	590lm	Negro-Black
220-240V~ 50/60Hz CRI≥ 80				Aluminio/Acrílico-Aluminium/Acrylic



DRIVER  
TUV

Registered N° 007663331-0010



SIRIO  
by Hugo Tejada

Lámparas de techo-Pendant lamp


Indoor



REFERENCE	K	LED WATT	LUMENS	FINISH
7311	3000K	24W	1770lm	Negro-Black
		220-240V~ 50/60Hz CRI≥ 80		
		Aluminio/Acrílico- Aluminium/Acrylic		



cables 6 x 1,8 m




DRIVER  
TÜV

Registered N° 007663331-0010




REFERENCE	K	LED WATT	LUMENS	FINISH
6825	3000K	21W	1475lm	Blanco Mate-Matt white
6826	3000K	21W	1475lm	Negro Mate-Matt black
220-240V~ 50/60Hz CRI≥ 80				Aluminio-Aluminium





REFERENCE	BULB NO INCLUDED	FINISH	DIAMETER (ø):
5622	1L x E27	Blanco mate-Matt White	ø 120
5624	1L x E27	Plata-Silver	ø 120
5623	1L x E27	Blanco mate-Matt White	ø 95
5625	1L x E27	Plata-Silver	ø 95
máx. 20W LED (No incl)		100-240V~50/60Hz Metal-Metal	






FLORÓN  
empotrable

Base empotrada para colgantes-Recessed base for pendants

Indoor





	REFERENCE	FINISH
New	7855	Blanco-White
New	7856	Negro-Black
New	7857	Plata-Silver
New	7858	Oro-Gold
New	7859	Cuero-Antique Brass
		Hierro-Iron








REFERENCE	BULB (No incl)	FINISH
7520	1L x GU10	Blanco arena-Sand white
7521	1L x GU10	Blanco arena-Sand white
7515	1L x GU10	Negro mate-Matt black
7516	1L x GU10	Negro mate-Matt black
máx. 10W LED (No incl) 100-240V ~50/60Hz Aluminio-Aluminium		



ref: 7520-7515



ref: 7521-7516



6284  
pág. 70




6717  
pág. 210



6282  
pág. 186



7522  
pág. 174



Bombillas recomendadas-Suggested bulbs


K	Wat LED	On/Off	Dimmable	Lumens
2700K	7W	R09254	R09257	510lm
3000K	7W	R09255	R09258	540lm
4000K	7W	R09256	R09259	570lm







REFERENCE	K	LED WATT	LUMENS	FINISH
7510	3000K	6 W	390lm	Negro arena-Sand black
7511	3000K	6 W	390lm	Negro arena-Sand black
220-240V ~ 50/60Hz CRI:≥ 80				Aluminio-Aluminium






TORCH

Sobremesa-Table lamp


Indoor



REFERENCE	K	LED WATT	LUMENS	FINISH
6737	3000K	11W	900lm	Blanco mate-Matt white
6738	3000K	11W	900lm	Negro mate-Matt black
220-240V~ 50/60Hz CRI:≥ 80				Aluminio-Aluminium








REFERENCE	K	LED WATT	LUMENS	FINISH
7464	3000K	18W	1380lm	Negro-Black
100-240V~50/60Hz CRI:≥ 80				Aluminium/Iron/Acrílico-Aluminium/Iron/Acrylic



REFERENCE	K	LED WATT	LUMENS	FINISH
6562	3000K	18W	1380lm	Blanco-White
100-240V~50/60Hz CRI:≥ 80				Aluminium/Iron/Acrílico-Aluminium/Iron/Acrylic







Touch  
switch  
3 Step-Dim




\* Cargador De Inducción Teléfono-Cell Phone Induction Charger

REFERENCE	K	LED WATT	LUMENS	FINISH
6715	3000K	6W	450lm	Blanco-White
6716	3000K	6W	450lm	Negro-Black
		220-240V~ 50/60Hz CRI:≥ 80	Aluminio/Metal-Aluminium/Metal	




6754  
pág. 58





REFERENCE	BULB (No incl)	FINISH
7522	1L x GU10	Blanco arena-Sand white
7517	1L x GU10	Negro mate-Matt black
máx. 10W LED (No incl)		100-240V~50/60Hz Acrílico-Acrylic



Bombillas recomendadas-Suggested bulbs

K	Wat LED	On/Off	Dimmable	Lumens
2700K	7W	R09254	R09257	510lm
3000K	7W	R09255	R09258	540lm
4000K	7W	R09256	R09259	570lm



6281  
pág. 186



6284  
pág. 70



6717  
pág. 210



7520  
pág. 164








REFERENCE	K	LED WATT	LUMENS	FINISH
7512	3000K	6W	390lm	Negro arena-Sand black
220-240V~ 50/60Hz CRI≥ 80				Aluminio-Aluminium



TORCH

Pie de Salón-Floor lamp

Indoor



360°

REFERENCE	K	LED WATT	LUMENS	FINISH
6735	3000K	25W	1950lm	Blanco mate-Matt white
6736	3000K	25W	1950lm	Negro mate-Matt black
220-240V~ 50/60Hz CRI:≥ 80				Aluminio-Aluminium



6703  
pág. 68



6828  
pág. 116





6826  
pág. 158




6738  
pág. 168







REFERENCE	K	LED WATT	LUMENS	FINISH	
7465	3000K	48W	3800lm	Negro-Black	Dimmable
		220-240V~50/60Hz CRI:≥ 80		Aluminium/Iron/Acrílico-Aluminium/Iron/Acrylic	



REFERENCE	K	LED WATT	LUMENS	FINISH	
6563	3000K	48W	3800lm	Blanco-White	Dimmable
		220-240V~50/60Hz CRI:≥ 80		Aluminium/Iron/Acrílico-Aluminium/Iron/Acrylic	

6230  
pág. 94




6560  
pág. 118

GLACIAR  
by Santiago Sevillano


Indoor




REFERENCE	K	LED WATT	LUMENS	FINISH	SIZES
7730	3000K	9W	700lm	Blanco-White	100
7731	4000K	9W	700lm	Blanco-White	100
7732	3000K	9W	700lm	Blanco-White	170
7733	4000K	9W	700lm	Blanco-White	170
7734	3000K	9W	700lm	Blanco-White	240
7735	4000K	9W	700lm	Blanco-White	240
220-240V ~ 50/60Hz CRI≥ 80				Acrílico-Arcylic	







REFERENCE	BULB (No incl)	FINISH
7294	1L x GU10	Blanco-White
7295	1L x GU10	Negro-Black
máx. 12W LED (No incl) 100-240V~50/60Hz Aluminio-Aluminium		



Bombillas recomendadas-Suggested bulbs


K	Wat LED	On/Off	Dimmable	Lumens
2700K	7W	R09254	R09257	510lm
3000K	7W	R09255	R09258	540lm
4000K	7W	R09256	R09259	570lm



Registered N° 007663331-0013




7937  
pág. 126




REFERENCE	BULB (No incl)	FINISH
6283	1L x GU10	Blanco mate-Matt white
6713	1L x GU10	Negro mate-Matt black
6282	2L x GU10	Blanco mate-Matt white
6712	2L x GU10	Negro mate-Matt black
6281	3L x GU10	Blanco mate-Matt white
6711	3L x GU10	Negro mate-Matt black
6280	4L x GU10	Blanco mate-Matt white
6710	4L x GU10	Negro mate-Matt black
máx. 10W LED (No incl) 100-240V~50/60Hz Aluminio-Aluminium		









REFERENCE	K	LED WATT	LUMENS	FINISH
6830	3000K	7W	520lm	Blanco arena-Sand white
6833	3000K	7W	520lm	Negro arena-Sand black
6832	4000K	7W	560lm	Blanco arena-Sand white
6831	4000K	7W	560lm	Negro arena-Sand black
220-240V~50/60Hz CRI:≥ 80				Aluminio-Aluminium







REFERENCE	BULB NO INCLUDED	FINISH
6015	1L x E27	Blanco-White
6016	1L x E27	Plata-Silver
máx. 20W LED (No incl)		100-240V ~50/60Hz Metal-Metal




Spheric Bulb: Ø45\*78




MiniStandard Bulb: Ø55\*103



Standard Bulb: Ø60\*108



R63 Bulb: Ø63\*105



R80 Bulb: Ø80\*116



6044  
pág. 210




5622  
pág. 160








REFERENCE	BULB NO INCLUDED	FINISH	DIAMETER (ø):
5626	1L x E27	Blanco-White	ø 120
5628	1L x E27	Plata-Silver	ø 120
5627	1L x E27	Blanco-White	ø 90
5629	1L x E27	Plata-Silver	ø 90
máx. 20W LED (No incl)		100-240V~50/60Hz Metal-Metal	




Standard Bulb: Ø60\*108




R90 Bulb: Ø90\*117




G95 Bulb: Ø95\*131




Sferic Bulb: Ø45\*78




MiniStandard Bulb: Ø55\*103



Standard Bulb: Ø60\*108



R63 Bulb: Ø63\*105



R80 Bulb: Ø80\*116






COLUMBRETES




Indoor



REFERENCE	K	LED WATT	LUMENS	FINISH
C0087	3000K	12W	1040lm	Blanco mate-Matt white
		220-240V~50/60Hz CRI:≥ 80		Aluminio-Aluminium






REFERENCE	K	LED WATT	LUMENS	FINISH
C0085	3000K	12W	1040lm	Blanco mate-Matt white
C0086	4000K	12W	1090lm	Blanco mate-Matt white
		220-240V~50/60Hz CRI:≥ 80		Aluminio-Aluminium






KAILUA

Indoor




REFERENCE	BULB (No incl)	FINISH
5633	1L x GU10	Blanco mate-Matt white
5632	2L x GU10	Blanco mate-Matt white
máx. 12W LED (No incl)		100-240V ~ 50/60Hz Aluminio-Aluminium




Bombillas recomendadas-Suggested bulbs

K	Wat LED	On/Off	Dimmable	Lumens
2700K	7W	R09254	R09257	510lm
3000K	7W	R09255	R09258	540lm
4000K	7W	R09256	R09259	570lm





REFERENCE	K	LED WATT	LUMENS	FINISH
5717	3000K	7W	500lm	Blanco mate-Matt white
5718	4000K	7W	560lm	Blanco mate-Matt white
220-240V~50/60Hz CRI:≥ 80				Aluminio- Aluminium












REFERENCE	K	LED WATT	LUMENS	FINISH
7315	3000K	35W	3500lm	Blanco-White
7316	4000K	35W	3850lm	Blanco-White
220-240V~ 50/60Hz CRI≥90				Aluminio-Aluminium

LENTES-LENS	
ref 7319 _13°	NOT INCLUDED
ref 7320 _24°	NOT INCLUDED
ref 7321 _38°	Included*




PANAL DE ABEJA-HONEYCOMB	
ref 7322	NOT INCLUDED



TIR  
LENS












REFERENCE	K	LED WATT	LUMENS	FINISH
7317	3000K	35W	3500lm	Negro-Black
7318	4000K	35W	3850lm	Negro-Black
220-240V ~ 50/60Hz CRI≥90				Aluminio-Aluminium

LENTES-LENS	
ref 7319 _13°	NOT INCLUDED
ref 7320 _24°	NOT INCLUDED
ref 7321 _38°	Included*



PANAL DE ABEJA-HONEYCOMB	
ref 7322	NOT INCLUDED



TIR  
LENS






PAGODA  
by David Villalba

Indoor



REFERENCE	BULB (No incl)	FINISH
7788	1L x GU10	Blanco mate-Matt white
7789	1L x GU10	Negro mate-Matt black
máx. 12W LED (No incl)		100-240V ~ 50/60Hz Metal-Metal



7787  
pág. 136



PAGODA  
by David Villalba

Colgante carril trifásico-Triphasic rail spot

Indoor


UGR<16 CRI≥90



REFERENCE	K	LED WATT	LUMENS	FINISH
7780	3000K	12,5W	950lm	Blanco-White
7782	3000K	12,5W	950lm	Negro-Black
7781	4000K	12,5W	1050lm	Blanco-White
7783	4000K	12,5W	1050lm	Negro-Black
220-240V~ 50/60Hz CRI≥90				Aluminio-Aluminium








REFERENCE	BULB (No incl)	FINISH
6044	1L x E27	Blanco-White
6045	1L x E27	Negro-Black
máx. 20W LED (No incl)		100-240V~50/60Hz Metal-Metal




6015  
pág. 190




5622  
pág. 160




Sferic Bulb: Ø45\*78




MiniStandard Bulb: Ø55\*103



Standard Bulb: Ø60\*108




R63 Bulb: Ø63\*105




R80 Bulb: Ø80\*116







REFERENCE	BULB NOT INCLUDED	FINISH
6717	1L x GU10	Blanco-White
6718	1L x GU10	Negro-Black
máx. 10W LED (No incl) 100-240V~ 50/60Hz Aluminio-Aluminium		




Bombillas recomendadas-Suggested bulbs

K	Wat LED	On/Off	Dimmable	Lumens
2700K	7W	R09254	R09257	510lm
3000K	7W	R09255	R09258	540lm
4000K	7W	R09256	R09259	570lm








REFERENCE	K	LED WATT	LUMENS	FINISH	OPTICAL Included*	ANGLE
7200	3000K	15W	1500lm	Blanco-White	7218	38°
7204	4000K	15W	1650lm	Blanco-White	7218	38°
7201	3000K	20W	2000lm	Blanco-White	7218	38°
7205	4000K	20W	2200lm	Blanco-White	7218	38°
7202	3000K	30W	3000lm	Blanco-White	7221	38°
7206	4000K	30W	3300lm	Blanco-White	7221	38°
7203	3000K	40W	4000lm	Blanco-White	7224	38°
7207	4000K	40W	4400lm	Blanco-White	7224	38°
220-240V~ 50/60HzCRI:≥ 90				Aluminio-Aluminium		

\* Reflector-Optic

REFERENCE 15/20W	REFERENCE 30W	REFERENCE 40W	BEAM ANGLE	INCLUDED
7216	7219	7222	15°	not included
7217	7220	7223	24°	not included
*7218	*7221	*7224	38°	Included*







REFERENCE	K	LED WATT	LUMENS	FINISH	OPTICAL Included*	ANGLE
7208	3000K	15W	1500lm	Negro-Black	7218	38°
7212	4000K	15W	1650lm	Negro-Black	7218	38°
7209	3000K	20W	2000lm	Negro-Black	7218	38°
7213	4000K	20W	2200lm	Negro-Black	7218	38°
7210	3000K	30W	3000lm	Negro-Black	7221	38°
7214	4000K	30W	3300lm	Negro-Black	7221	38°
7211	3000K	40W	4000lm	Negro-Black	7224	38°
7215	4000K	40W	4400lm	Negro-Black	7224	38°
220-240V ~ 50/60HzCRI:≥ 90				Aluminio-Aluminium		

\* Reflector-Optic


REFERENCE 15/20W	REFERENCE 30W	REFERENCE 40W	BEAM ANGLE	INCLUDED
7216	7219	7222	15°	not included
7217	7220	7223	24°	not included
*7218	*7221	*7224	38°	Included*






FIJI


LED 15W 3000K 38°




LED 15W 4000K 38°




LED 20W 3000K 38°




LED 20W 4000K 38°




LED 30W 3000K 38°




LED 30W 4000K 38°



LED 40W 3000K 38°



LED 40W 4000K 38°



CARRILES trifásicos

Carriles trifásicos-Triphasic tracks

Indoor

CARRIL DE SUPERFICIE-SURFACE MOUNTED TRACK

XTS 41002 Negro-Black


XTS 41003 Blanco-White

Track length 1000 mm

XTS 42002 Negro-Black

XTS 42003 Blanco-White

Track length 2000 mm



CARRIL DE EMPOTRAR-RECESSED TRACK

XTSF41002 Negro-Black


XTSF41003 Blanco-White

Track length 1000 mm




XTSF42002 Negro-Black

XTSF 42003 Blanco-White

Track length 2000 mm



Power Conductor Cross-Section: 4,0mm<sup>2</sup>




Carriles trifásicos-Triphasic tracks

FINAL ALIMENTADOR POLARIDAD DERECHA-END FEED POLARITY RIGHT

XTS 112 Negro-Black

XTS 113 Blanco-White



FINAL ALIMENTADOR POLARIDAD IZQUIERDA-END FEED POLARITY LEFT

XTS 122 Negro-Black

XTS 123 Blanco-White



TAPA FINAL-END CAP

XTS 412 Negro-Black

XTS 413 Blanco-White



PLACA PARA CUBRIR EN CARRILES EMPOTRADOS -PLATE TO COVER IN RECESSED TRACKS

XTSF 102 Negro-Black XTS112/XTS122/XTS142

XTSF 103 Blanco-White XTS113/XTS123/XTS143



XTSF 302 Negro-Black XTS342/XTS352

XTSF 303 Blanco-White XTS343/XTS353



LEVA FIJACIÓN TECHO FUNDICIÓN PARA CARRILES SUPERFICIE-STANDARD CLAMP DIE CAST FOR SURFACE TRACK

SKB 122 Negro-Black

SKB 123 Blanco-White



KIT SUSPENSION CARRIL 1,5 M -SUSPENSION KIT 1,5 M

SPW11SK 215 length 1500 mm Negro-Black

SPW11SK 315 length 1500 mm Blanco-White





CARRILES trifásicos

ALIMENTADOR INTERMEDIO RECTO-MIDDLE FEED STRAIGHT

XTS 142 Negro-Black

XTS 143 Blanco-White



CONECTOR INTERMEDIO RECTO-MIDDLE STRAIGHT CONNECTOR

XTS 212 Negro-Black

XTS 213 Blanco-White



CONECTOR ESQUINA AJUSTABLE-ADJUSTABLE CORNER CONNECTOR

XTS 242 Negro-Black


XTS 243 Blanco-White



CONEXIÓN ALIMENTADOR EN L POLARIDAD INTERNA - L FEED POLARITY INTERNAL

XTS 342 Negro-Black


XTS 343 Blanco-White



CONEXIÓN ALIMENTADOR EN L POLARIDAD EXTERNA - L FEED POLARITY EXTERNAL

XTS 352 Negro-Black


XTS 353 Blanco-White



CONEXIÓN ALIMENTADOR EN X - X FEED

XTS 382 Negro-Black

XTS 383 Blanco-White



CONEXIÓN ALIMENTADOR EN T- T FEED


XTS 362 Negro-Black

XTS 363 Blanco-White



XTS 372 Negro-Black

XTS 373 Blanco-White




XTS 392 Negro-Black

XTS 393 Blanco-White



XTS 402 Negro-Black

XTS 403 Blanco-White





— Polarity Line

GUINCHO

Empotrable-Recessed


Indoor  
IP54




REFERENCE	K	LED WATT	LUMENS	FINISH
7080	2700K	3W	210lm	Blanco arena-Sand white
7081	2700K	3W	210lm	Negro arena-Sans black
6855	3000K	3W	210lm	Blanco arena-Sand white
6856	3000K	3W	210lm	Negro arena-Sans black
6859	4000k	3W	210lm	Blanco arena-Sand white
6860	4000k	3W	210lm	Negro arena-Sans black
7082	2700K	5W	410lm	Blanco arena-Sand white
7083	2700K	5W	410lm	Negro arena-Sans black
6857	3000K	5W	410lm	Blanco arena-Sand white
6858	3000K	5W	410lm	Negro arena-Sans black
6861	4000k	5W	410lm	Blanco arena-Sand white
6862	4000k	5W	410lm	Negro arena-Sans black
200-240V~ 50/60Hz CRI:≥ 80				Aluminio-Aluminium




6855-6856




6857-6858



7080-7081



7082-7083







GUINCHO GU10

Empotrable-Recessed

Indoor



REFERENCE	BULB NO INCLUDED	FINISH
7535	1 × GU10	Blanco arena-Sand white
7536	1 × GU10	Negro arena-Sand black
GU10 máx 10W Led 100-240V~ 50/60Hz Aluminio-Aluminium		



K	Wat LED	On/Off	Dimmable	Lumens
2700K	7W	R09254	R09257	510lm
3000K	7W	R09255	R09258	540lm
4000K	7W	R09256	R09259	570lm



70mm



NOT INCLUDED



garantía mantenido 2 años WARRANTY 2 YEARS






IP20








	REFERENCE	K	LED WATT	LUMENS	FINISH
New	7829	2700K	7W	610lm	Blanco-White
New	7831	2700K	7W	610lm	Negro-Black
	6400	3000K	7W	610lm	Blanco-White
New	7833	3000K	7W	610lm	Negro-Black
	6401	4000K	7W	630lm	Blanco-White
New	7830	2700K	12W	1020lm	Blanco-White
New	7832	2700K	12W	1020lm	Negro-Black
	6402	3000K	12W	1020lm	Blanco-White
New	7834	3000K	12W	1020lm	Negro-Black
	6403	4000K	12W	1080lm	Blanco-White
220-240V~ 50/60Hz CRI:≥ 80					Aluminio ABS -Aluminium







	REFERENCE	K	LED WATT	LUMENS	FINISH
New	7827	2700K	3W	210lm	Blanco-White
New	7828	2700K	3W	210lm	Negro-Black
	7451	3000K	3W	210lm	Blanco-White
	7453	3000K	3W	210lm	Negro-Black
	7452	4000K	3W	220lm	Blanco-White
	7454	4000K	3W	220lm	Negro-Black
100-240V~ 50/60Hz CRI:≥ 90					Aluminio-Aluminium







C0073-C0074



C0071-C0072

REFERENCE	K	LED WATT	LUMENS	FINISH
C0071	3000K	7W	610lm	Blanco mate-Matt white
C0072	4000K	7W	650lm	Blanco mate-Matt white
C0073	3000K	12W	1040lm	Blanco mate-Matt white
C0074	4000K	12W	1080lm	Blanco mate-Matt white
220-240V ~ 50/60Hz CRI:≥ 80				Aluminio-Aluminium



C0077-C0078




C0075-C0076




C0079-C0080

REFERENCE	K	LED WATT	LUMENS	FINISH
C0075	3000K	7W	610lm	Blanco mate-Matt white
C0076	4000K	7W	650lm	Blanco mate-Matt white
C0079	3000K	7W	610lm	Blanco mate-Matt white
C0080	4000K	7W	650lm	Blanco mate-Matt white
C0077	3000K	12W	1040lm	Blanco mate-Matt white
C0078	4000K	12W	1080lm	Blanco mate-Matt white
220-240V ~ 50/60Hz CRI:≥ 80				Aluminio-Aluminium


C0077-C0078




C0075-C0076



C0079





C0080







# FORMENTERA



C0077





C0078





C0075



C0076




C0080



Indoor







REFERENCE	K	LED WATT	LUMENS	FINISH
C0041	3000K	7W	540lm	Blanco mate-Matt white
C0042	4000K	7W	540lm	Blanco mate-Matt white
C0047	3000K	12W	1080lm	Blanco mate-Matt white
C0048	4000K	12W	1080lm	Blanco mate-Matt white
C0043	3000K	24W	2160lm	Blanco mate-Matt white
C0044	4000K	24W	2160lm	Blanco mate-Matt white
C0049	3000K	30W	2550lm	Blanco mate-Matt white
C0050	4000K	30W	2600lm	Blanco mate-Matt white
220-240V~ 50/60Hz CRI:≥ 80				Aluminio-Aluminium







MEDANO

Empotrable-Recessed

Indoor  
UGR<19



REFERENCE	K	LED WATT	LUMENS	FINISH
6398	3000K	12W	1100lm	Blanco mate-Matt white
6399	4000K	12W	1200lm	Blanco mate-Matt white
6395	3000K	21W	1900lm	Blanco mate-Matt white
6396	4000K	21W	2100lm	Blanco mate-Matt white
SPCC-PBT/PC 220-240V~ 50/60Hz CRI:≥ 80 Aluminio-Aluminium				







SAONA

Empotrable-Recessed


Indoor



REFERENCE	K	LED WATT	LUMENS	FINISH
C0184	3000K	6W	520lm	Blanco mate-Matt white
C0180	4000K	6W	540lm	Blanco mate-Matt white
C0185	3000K	12W	990lm	Blanco mate-Matt white
C0181	4000K	12W	1080lm	Blanco mate-Matt white
SPCC-PBT/PC		220-240V~ 50/60Hz CRI:≥ 80		Aluminio-Aluminium




REFERENCE	K	LED WATT	LUMENS	FINISH
C0186	3000K	18W	1580lm	Blanco mate-Matt white
C0182	4000K	18W	1620lm	Blanco mate-Matt white
C0187	3000K	24W	2090lm	Blanco mate-Matt white
C0183	4000K	24W	2200lm	Blanco mate-Matt white
SPCC-PBT/PC		220-240V~ 50/60Hz CRI:≥ 80		Aluminio-Aluminium









REFERENCE	K	LED WATT	LUMENS	FINISH
C0194	3000K	6W	520lm	Blanco mate-Matt white
C0190	4000K	6W	540lm	Blanco mate-Matt white
C0195	3000K	12W	990lm	Blanco mate-Matt white
C0191	4000K	12W	1080lm	Blanco mate-Matt white
SPCC-PBT/PC		220-240V~ 50/60Hz CRI:≥ 80		Aluminio-Aluminium



REFERENCE	K	LED WATT	LUMENS	FINISH
C0196	3000K	18W	1580lm	Blanco mate-Matt white
C0192	4000K	18W	1620lm	Blanco mate-Matt white
C0197	3000K	24W	2090lm	Blanco mate-Matt white
C0193	4000K	24W	2200lm	Blanco mate-Matt white
SPCC-PBT/PC		220-240V~ 50/60Hz CRI:≥ 80		Aluminio-Aluminium



GRACIOSA

Empotrable-Recessed

Indoor





REFERENCE	K	LED WATT	LUMENS	FINISH	SIZES
6392	3000K	15,3W	1100lm	Blanco mate-Matt white	Ø180
6397	4000K	10,8W	850lm	Blanco mate-Matt white	Ø146
220-240V~ 50/60Hz CRI:≥ 80				Aluminio-Aluminium	



GRACIOSA

REFERENCE	K	LED WATT	LUMENS	FINISH	SIZES
6390	3000K	24,5W	1900lm	Blanco mate-Matt white	Ø235
220-240V~ 50/60Hz CRI:≥ 80				Aluminio-Aluminium	





BÁSICO GU10

Empotrable-Recessed

Indoor

C0002



REFERENCE	BULB NO INCLUDED	FINISH
C0001	1 × GU10	Nickel Satinado/Cromo-Satin Nickel/Chrome
C0002	1 × GU10	Nickel Satinado/Cromo-Satin Nickel/Chrome
C0003	1 × GU10	Blanco mate-Matt white
C0004	1 × GU10	Blanco mate-Matt white
C0005	1 × GU10	Aluminio Pulido-Polished Aluminium
C0006	1 × GU10	Aluminio Pulido-Polished Aluminium
C0007	1 × GU10	Negro mate-Matt black
C0008	1 × GU10	Negro mate-Matt black
GU10 máx 12W Led		100-240V~ 50/60Hz Aluminio-Aluminium



Bombillas recomendadas-Suggested bulbs

K	Wat LED	On/Off	Dimmable	Lumens
2700K	7W	R09254	R09257	510lm
3000K	7W	R09255	R09258	540lm
4000K	7W	R09256	R09259	570lm



BÁSICO GU10

Empotrable-Recessed

Indoor



REFERENCE	BULB NO INCLUDED	FINISH
7740	1 × GU10	Nickel Satinado/Cromo-Satin Nickel/Chrome
7741	1 × GU10	Blanco mate-Matt white
7742	1 × GU10	Aluminio Pulido-Polished Aluminium
7743	1 × GU10	Negro mate-Matt black
GU10 máx 12W Led		100-240V~ 50/60Hz Aluminio-Aluminium



Bombillas recomendadas-Suggested bulbs

K	Wat LED	On/Off	Dimmable	Lumens
2700K	7W	R09254	R09257	510lm
3000K	7W	R09255	R09258	540lm
4000K	7W	R09256	R09259	570lm







COMFORT GU10

Empotrable-Recessed


Indoor



REFERENCE	BULB NO INCLUDED	FINISH
C0160	1 × GU10	Blanco mate-Matt white
C0161	1 × GU10	Plata mate-Matt silver
C0164	1 × GU10	Negro mate-Matt black
GU10 máx 12W Led		100-240V~ 50/60Hz Aluminio-Aluminium



REFERENCE	BULB NO INCLUDED	FINISH
C0162	1 × GU10	Blanco mate-Matt white
C0163	1 × GU10	Plata mate-Matt silver
C0165	1 × GU10	Negro mate-Matt black
GU10 máx 12W Led		100-240V~ 50/60Hz Aluminio-Aluminium



C0160









6902



6903



REFERENCE	BULB NO INCLUDED	FINISH
6902	1 × GU10	Blanco mate-Matt white
6903	1 × GU10	Negro Mate-Matt Black
6900	1 × GU10	Blanco mate-Matt white
6901	1 × GU10	Negro Mate-Matt Black
GU10 máx 12W Led 100-240V~ 50/60Hz Aluminio-Aluminium		






Bombillas recomendadas-Suggested bulbs

K	Wat LED	On/Off	Dimmable	Lumens
2700K	7W	R09254	R09257	510lm
3000K	7W	R09255	R09258	540lm
4000K	7W	R09256	R09259	570lm




6900




6901







REFERENCE	BULB NO INCLUDED	FINISH
6839	1 × GU10	Blanco mate-Matt white
6840	1 × GU10	Negro mate-Matt black
6843	1 × GU10	Blanco mate-Matt white
6844	1 × GU10	Negro mate-Matt black
6841	1 × GU10	Blanco mate-Matt white
6842	1 × GU10	Negro mate-Matt black
6845	1 × GU10	Blanco mate-Matt white
6846	1 × GU10	Negro mate-Matt black
GU10 máx 12W Led		100-240V~ 50/60Hz PCB by samsung








REFERENCE	BULB NO INCLUDED	FINISH
6835	1 × GU10	Blanco mate-Matt white
6837	1 × GU10	Blanco mate-Matt white
6838	1 × GU10	Negro mate-Matt black
GU10 máx 12W Led		100-240V~ 50/60Hz PCB by samsung







REFERENCE	K	LED WATT	LUMENS	FINISH
C0083	3000K	7W	490lm	Blanco mate-Matt white
C0084	4000K	7W	520lm	Blanco mate-Matt white
220-240V ~ 50/60Hz CRI:≥ 80				Aluminio-Aluminium








REFERENCE	K	LED WATT	LUMENS	FINISH
C0081	3000K	7W	610lm	Blanco mate-Matt white
C0082	4000K	7W	640lm	Blanco mate-Matt white
220-240V ~ 50/60Hz CRI:≥ 80				Aluminio-Aluminium





3000K




4000K









REFERENCE	BULB NO INCLUDED	FINISH
6405	1 × GU10	Blanco mate-Matt white
6406	1 × GU10	Aluminio Plata-Silver Aluminium
GU10 máx 12W Led 100-240V~ 50/60Hz Aluminio-Aluminium		



Bombillas recomendadas-Suggested bulbs

K	Wat LED	On/Off	Dimmable	Lumens
2700K	7W	R09254	R09257	510lm
3000K	7W	R09255	R09258	540lm
4000K	7W	R09256	R09259	570lm




REFERENCE	BULB NO INCLUDED	FINISH	SIZES
6810	1 × GU10	Blanco mate-Matt white	ø 8.5×4.5cm
6811	1 × GU10	Negro mate-Matt black	ø 8.5×4.5cm
6812	1 × GU10	Blanco mate-Matt white	4.5×8.5×8.5cm
6813	1 × GU10	Negro mate-Matt black	4.5×8.5×8.5cm
GU10 máx 12W Led 100-240V~ 50/60Hz Aluminio-Aluminium			





TIRAS-STRIPS

Tira LED flexible para uso interior IP20  
IP20 Flexible LED strip for indoor lighting



Características técnicas / Technical characteristics


Ref.	Color Colour	Color temp. Colour Tª	Tensión DC voltage DC	Ud. LED metro LED units meter	Potencia por metro Power meter	Eficiencia luminosa metro Luminous efficacy meter	Eficiencia luminosa vatio Luminous efficacy watt	CRI	SDCM	Ancho Wide	Corte Cut	Ud. LED corte LED units cut	Metros rollo Meters reel	Protección Protection
		K	V		W/m	lm/m*	lm/W			mm	mm	pcs	m	IP
7366	●	2700	24	240	19,2	1400	73	≥ 90	< 3	10	25	6	5	20
7367	●	3000	24	240	19,2	1470	77	≥ 90	< 3	10	25	6	5	20
7368	○	4000	24	240	19,2	1540	80	≥ 90	< 3	10	25	6	5	20



24V CRI:≥ 90 tc<65°

TIRAS-STRIPS

Tira LED flexible para uso interior. IP20  
IP20 Flexible LED strip for indoor use



Características técnicas / Technical characteristics


Ref.	Color Colour	Color temp. Colour Tª	Tensión DC voltage DC	Ud. LED metro LED units meter	Potencia por metro Power meter	Eficiencia luminosa metro Luminous efficacy meter	Eficiencia luminosa vatio Luminous efficacy watt	CRI	SDCM	Ancho Wide	Corte Cut	Ud. LED corte LED units cut	Metros rollo Meters reel	Protección Protection
		K	V		W/m	lm/m*	lm/W			mm	mm	pcs	m	IP
7360	●	2700	24	60	9,6	650	68	≥ 90	< 3	10	100	6	5	20
7361	●	3000	24	60	9,6	685	71	≥ 90	< 3	10	100	6	5	20
7362	○	4000	24	60	9,6	715	74	≥ 90	< 3	10	100	6	5	20



24V CRI:≥ 90 tc<65°

TIRAS-STRIPS

Tira LED flexible para uso interior. IP20  
IP20 Flexible LED strip for indoor use



Características técnicas / Technical characteristics



Ref.	Color Colour	Color temp. Colour Tª	Tensión DC voltage DC	Ud. LED metro LED units meter	Potencia por metro Power meter	Eficiencia luminosa metro Luminous efficacy meter	Eficiencia luminosa vatio Luminous efficacy watt	CRI	SDCM	Ancho Wide	Corte Cut	Ud. LED corte LED units cut	Metros rollo Meters reel	Protección Protection
		K	V		W/m	lm/m*	lm/W			mm	mm	pcs	m	IP
7363	●	2700	24	120	14,4	1010	70	≥ 90	< 3	8	50	6	5	20
7364	●	3000	24	120	14,4	1060	74	≥ 90	< 3	8	50	6	5	20
7365	○	4000	24	120	14,4	1110	77	≥ 90	< 3	8	50	6	5	20



24V CRI:≥ 90 tc<65°

TIRAS-STRIPS

Tira LED flexible para uso exterior IP65  
IP65 Flexible LED strip for outdoor lighting



Características técnicas / Technical characteristics

Ref.	Color Colour	Color temp. Colour Tª	Tensión DC voltage DC	Ud. LED metro LED units meter	Potencia por metro Power meter	Eficiencia luminosa metro Luminous efficacy meter	Eficiencia luminosa vatio Luminous efficacy watt	CRI	SDCM	Ancho Wide	Corte Cut	Ud. LED corte LED units cut	Metros rollo Meters reel	Protección Protection
		K	V		W/m	lm/m*	lm/W			mm	mm	pcs	m	IP
7369	●	3000	24	120	14,4	950	66	≥ 90	< 3	10	50	6	5	65
7370	○	4000	24	120	14,4	995	69	≥ 90	< 3	10	50	6	5	65

Accesorios de corte IP no incluidos / IP Cutting accessories not included



- 7406 Conexión estanca DC/Waterproof connection
- 7404 Pegamento silicona/Silicone glue
- 7403 Final silicona con agujeros  
Silicone end cap w/holes
- 7405 Final silicona/Silicone End cap



24V CRI:≥ 90 tc<65°

















PERFILES – PROFILES

Perfil para tiras LED  
Profile for LED strips


Indoor




7381 Blanco-White	7382 Negro-Black	7383 Aluminio-Aluminium
Piezas incluidas/Included pieces	Piezas incluidas/Included pieces	Piezas incluidas/Included pieces
2 m  Perfil+difusor/Profile+diffuser	2 m  Perfil+difusor/Profile+diffuser	2 m  Perfil+difusor/Profile+diffuser
2 × 7384 	2 × 7385 	2 × 7386 
2 × 7387 	2 × 7388 	2 × 7389 
4 × 7391 	4 × 7391 	4 × 7390 



Tapa/End cap



Clip PC transparent



Clip aluminium









Aluminio+PCB/Aluminium+PCB

PERFILES – PROFILES


Perfil para tiras LED  
Profile for LED strips




7392 Blanco-White	7393 Negro-Black	7394 Aluminio-Aluminium
Piezas incluidas/Included pieces	Piezas incluidas/Included pieces	Piezas incluidas/Included pieces
2 m  Perfil+difusor/Profile+diffuser	2 m  Perfil+difusor/Profile+diffuser	2 m  Perfil+difusor/Profile+diffuser
2 × 7395 	2 × 7396 	2 × 7397 
2 × 7398 	2 × 7399 	2 × 7400 
4 × 7402 	4 × 7402 	4 × 7401 



Tapa/End cap




Clip PC transparent



Clip aluminium



Aluminio+PCB/Aluminium+PCB



PERFILES - PROFILES

Perfil empotrado para suelo  
LED Strip Profile recessed in ground



8064 Aluminio-Aluminium

Piezas incluidas/Included pieces

2 m






Perfil+difusor/Profile+diffuser

2 x 8065



2 x 8066



Aluminio+PCB/Aluminium+PCB

Indoor











PERFILES - PROFILES

Perfil para esquinas  
Profiles for corners

Indoor



7417 Blanco-White		7418 Negro-Black	
Piezas incluidas/Included pieces		Piezas incluidas/Included pieces	
2 m		2 m	
Perfil+difusor/Profile+diffuser		Perfil+difusor/Profile+diffuser	
2 x 8060	 	2 x 8061	 
2 x 8062	 	2 x 8063	 
4 x 7419		4 x 7419	



Aluminio+PCB/Aluminium+PCB

PERFILES - PROFILES

Perfil empotrable para tiras led  
Recessed profile for led strips



8070 Aluminio-Aluminium

Piezas incluidas/Included pieces

2 m






Perfil+difusor/Profile+diffuser

2 x 8071



2 x 8072



Indoor




Aluminio+PCB/Aluminium+PCB



PERFILES – PROFILES

Perfil empotrable para tiras led  
Recessed profile for led strips

Indoor



8067 Aluminio-Aluminium

Piezas incluidas/Included pieces

2 m






Perfil+difusor/Profile+diffuser


2 x 8068



2 x 8069



Aluminio+PCB/Aluminium+PCB




PERFILES-PROFILES


Perfiles Empotrables para tiras LED  
Recessed Profile for LED strips




7407 Blanco-White	7408 Negro-Black	7409 Aluminio-Aluminium
Piezas incluidas/Included pieces	Piezas incluidas/Included pieces	Piezas incluidas/Included pieces
2 m 	2 m 	2 m 
Perfil+difusor/Profile+diffuser	Perfil+difusor/Profile+diffuser	Perfil+difusor/Profile+diffuser
2 x 7410 	2 x 7411 	2 x 7412 
2 x 7413 	2 x 7414 	2 x 7415 
4 x 7416 	4 x 7416 	4 x 7416 



Tapa/End cap



Clip aluminium




Aluminio+PCB/Aluminium+PCB

Indoor

ALIMENTADORES-DRIVERS

Tension constante 24v IP67  
IP67 24v Constant voltage



Características técnicas / Technical characteristics

Ref.	Art.-No	Tensión nominal de entrada Nominal input voltage	Rango de potencia en módulo Output power range	Tensión de salida DC Output voltage DC	Corriente de salida máxima Maximum output current	Factor de potencia Power factor	Frecuencia Frequency	Temp. máx. envolvente Max temp.at tc point	Temp. funcionamiento Operating temp.	Protección Protection
		Vac	W	Vdc	A	λ	Hz	tc (°C)	ta (°C)	IP
7378	SPE100-24VLP	200-240V	0-100	24	4.17	≥ 0,95	50/60	90°	-20...+60°	67
7379	SPE150-24VLP	200-240V	0-150	24	6.25	≥ 0,95	50/60	90°	-20...+60°	67
7380	SPE200-24VLP	200-240V	0-200	24	8.33	≥ 0,95	50/60	90°	-20...+60°	67



SELV





ALIMENTADORES-DRIVERS



Tension constante 24v  
24v Constant voltage



Indoor

ALIMENTADORES-DRIVERS

Tension constante 24v finos  
24v Constant voltage slim



Características técnicas / Technical characteristics

Ref.	Art.-No	Tensión nominal de entrada Nominal input voltage	Rango de potencia en módulo Output power range	Tensión de salida DC Output voltage DC	Corriente de salida máxima Maximum output current	Factor de potencia Power factor	Frecuencia Frequency	Temp. máx. envolvente Max temp.at tc point	Temp. funcionamiento Operating temp.	Protección Protection
		Vac	W	Vdc	A	$\lambda$	Hz	tc (°C)	ta (°C)	IP
7371	SE30-24VL	200-240V	0-30	24	1.25	$\geq 0,9$	50/60	80°	-20...+45°	20
7372	SE60-24VL	200-240V	0-60	24	2.5	$\geq 0,95$	50/60	90°	-20...+45°	20
7373	SE100-24VL	220-240V	0-100	24	4.17	$\geq 0,95$	50/60	90°	-20...+45°	20
7374	SE150-24VL	220-240V	0-150	24	6.25	$\geq 0,9$	50/60	90°	-20...+45°	20
7375	SNP250-24VL	200-240V	0-250	24	10.4	$\geq 0,95$	50/60	90°	-20...+45°	20

Características técnicas / Technical characteristics

Ref.	Art.-No	Tensión nominal de entrada Nominal input voltage	Rango de potencia en módulo Output power range	Tensión de salida DC Output voltage DC	Corriente de salida máxima Maximum output current	Factor de potencia Power factor	Frecuencia Frequency	Temp. máx. envolvente Max temp.at tc point	Temp. funcionamiento Operating temp.	Protección Protection
		Vac	W	Vdc	A	$\lambda$	Hz	tc (°C)	ta (°C)	IP
7376	SS30-24VF	220-240V	0-30	24	1.25	$\geq 0,95$	50/60	85°	-20...+45°	20
7377	SS60-24VF	200-240V	0-60	24	2.5	$\geq 0,9$	50/60	80°	-20...+50°	20




SISTEMAS CONTROL-CONTROL SYSTEMS

Controlador LED DIM-TW  
DIM-TW LED Controller



El controlador PRO-DIMTW-C01 permite controlar la iluminación de una tira LED monocolor o de Blanco Dinámico (TW) desde un mando a distancia.

El controlador puede ser sincronizado con hasta 8 mandos a distancia simultáneamente. Cada mando a distancia puede controlar hasta 4 controladores diferentes de manera autónoma



PRO-DIMTW-C01

PRO-DIMTW-C01 can control single colour (1CH) or Tunable White (2CH) LED Strips from an RF remote control.

The controller could be linked with up to 8 remotes at the same time. Each remote can control 4 controllers independently.

Accesorios / Accessories


Ref 9955911 PRO-DIM-R01



Esquema de conexión / Connection diagram

Ref.	Tensiones de entrada y salida Input-output Voltage	Tipo de regulación Control signal	Intensidad máx. de salida Max output current	Potencia máx. de salida Max output powewr	Tipo tira Led Led strip type	Control a través de Tipo Control made by
	V	mA	A	12V 24V		Mando a distancia RF
9955912	12-24	PWM	3 x 5A DIM 2x 5A TW	60W CH 120 W CH	Monocolor (1CH-DIM) TW (2CH)	RF Remote control

Modos de control y funcionamiento / Functions and control modes



SISTEMAS CONTROL-CONTROL SYSTEMS

Mando a distancia DIM Monocolor  
DIM Single Colour remote control



El mando PRO-DIM-R01 puede controlar hasta un máximo de 20 receptores.

Permite regular la intensidad de la luz.

Permite controlar hasta 4 zonas independientes.

Cada zona puede ser de uno o más controladores

Permite programar 2 escenas en memoria.


The PRO-DIM-R01 remote control can control a maximum of 20 receivers.

Allows regulation of lighting intensity.

Can control up to 4 independent zones.

Each zone can be with one or more controllers.

Can program 2 saving scenes.




Accesorios / Accessories

Ref 9955912 PRO-DIMTW-C01



Características técnicas / Technical characteristics

Ref.	Alimentación Power	Frecuencia de operación Operation frequency	Tipo de tira LED LED strip type	Alcance máx. interior (Sin paredes) Max. Range (Without walls)	Compatible con Compatible with
		Mhz		m	
9955911	3xAAA/LR03 1,5V batteries/ pilas	434/869	TW (2CH) DIM / monocolor (1CH)	20	SPU-DIM-C01





SISTEMAS CONTROL-CONTROL SYSTEMS


SPU-DIM-C01

SISTEMAS CONTROL-CONTROL SYSTEMS

SPU-DIM-R01

Controlador LED para pulsadores estándar y/o mando a distancia

LED Controller for standard push switch and/or remote control



El controlador SPU-DIM-C01 permite controlar la iluminación de una tira LED monocolor desde un pulsador estándar de cualquier fabricante. Pueden controlarse las tiras LED manteniendo la misma familia de mecanismos que en el resto de la instalación en la que se integre.

También puede controlarse con los mecanismos RF SPU. Son mecanismos sin cables de instalación muy sencilla, pegar o atornillar y que funcionan con pila de 3 años de duración. Permite controlar los LEDs fijando el mecanismo en cualquier superficie.

El controlador puede ser gobernado por varios pulsadores (ver esquema de conexión) y hasta 8 mecanismos RF SPU a la vez. Puede funcionar con los dos sistemas de control de manera simultánea (pulsador conectado por cable y mecanismos RF) o sólo con uno de ellos.

STO-DIM-C01 can control single colour LED strips from a standard push switch from any manufacturer. LED strips can be controlled keeping the same kind of switches as the rest of the installation.


It can also be controlled with the RF SPU switches. These switches are wireless, work with a 3-year-life battery and are very easy to install: just screw or stick in any surface.

Controller can be managed by several push switches (see wiring diagram) and up to 8 RF SPU switches at the same time. It can work with two control systems (standard switches or RF switches) simultaneously or only with one of them.

Características técnicas / Technical characteristics

Ref.	Tensiones de entrada y salida Input-output Voltage	Tipo de regulación Control signal	Intensidad máx. de salida Max output current	Potencia máx. de salida Max output powewr	Tipo tira Led Led strip type	Control a través de Tipo Control made by
	V	mA	A	12V 24V 36V		Pulsador standard y/o mecanismo RF
9955901	12-24-36	PWM	1x8	96 W 192 W 288 W	MONOC. DIM (1CH)	Standard push switch and/or RF Switch

Modos de control y funcionamiento / Functions and control modes



Mecanismo RF

RF Switch PUSH SYSTEM




Mecanismo RF pequeño y versátil que permite encender, apagar y regular una instalación de tira LED monocolor.

Puede ser fijado a una pared mediante tornillos o pegado (cinta de doble cara incluida). También lleva un imán para fijarse con facilidad en superficies metálicas.

Su reducido tamaño permite que pueda ser llevado en un bolsillo como mando a distancia. Está alimentado por una pila de tipo CR2025 de larga duración.

Fijación: Tornillos / iman.



Small and versatile RF switch which allows to switch ON/OFF and dim a single colour LED strip.

Can be easily fixed to a wall with screws or sticked (double side tape included). Also comes with a small magnet to be fixed easily on metalic surfaces.

Its small size allows to take it in a pocket as a remote control. It 's powered with a long life CR2025 battery.

Fixing: Screw / magnet.

Controlador compatible / Controller compatible with


Ref 9955901 SPU-DIM-C01



Características técnicas / Technical characteristics

Ref.	Alimentación Power	Frecuencia de operación Operation frequency	Tipo de tira LED LED strip type	Alcance máx. interior (Sin paredes) Max. Range (Without walls)	Compatible con Compatible with
		Mhz		m	
9955905	CR2025 3V battery / pila	434/869	DIM (1CH)	30	SPU-DIM-C01

Características técnicas / Technical characteristics




SISTEMAS CONTROL-CONTROL SYSTEMS

Digital dimmer, 1 dirección digital, 4 canales  
Digital dimmer, 1 digital address, 4 channels

DAL-MULTI-C02

12-36V DC



Permite la regulación de tiras LED desde cualquier sistema de control compatible con protocolo DALI. Sólo necesita conexión al bus DALI y asignar al controlador la dirección DALI desde la que se hará el control de las tiras.

Control de tiras LED monocolor.

Incluye pantalla y botones para ver y asignar fácilmente la dirección DALI.

El mismo modelo es válido para pilotar de 1 a 4 canales de forma sincronizada. Cada canal de salida tiene una capacidad de 5A.

0-100% rango de regulación según curva.

*This device allows to control LED strips from any control system compatible with DALI protocol. Only needs a connexion to the DALI bus and assign the device the DALI address to control the strips.*

*Control of LED single colour strips.*

*Includes screen and buttons to see and assign easily the DALI address.*


*The same model works from 1 to 4 channel synchronously. Each channel has a current output of 5A*

*0-100% dimming range via logarithmic curve.*

Características técnicas / Technical characteristics

Ref.	Tensiones de entrada y salida Input-output Voltage	Tipo de regulación Control signal	Intensidad máx. de salida Max output current	Potencia máx. de salida Max output powewr	Tipo tira Led Led strip type	Control a través de Tipo Control made by
	Vdc	mA	A	12V 24V 36V		
9955921	12-24-36	PWM	4 ch × 5A	240 W 480 W 720 W (4 × 60) (4 × 120) (4 × 180)	DIM	DALI

Esquema de conexión / Connection diagram



SISTEMAS CONTROL-CONTROL SYSTEMS

Controlador LED para pulsadores estándar y/o mando a distancia  
LED Controller for standard push switch and/or remote control



eBLUE MULTI4 es un regulador PWM de cuatro canales controlable por Bluetooth para cargas LED de tensión constante, tales como tiras y módulos LED de tensión constante.

eBLUE MULTI4 puede controlar hasta cuatro canales. La corriente de salida máxima es 6A, la cual puede ser dividida libremente entre 1-4 canales.

Dimensiones muy reducidas para su instalación.

Protegido contra sobrevoltages, sobre corriente y cortocircuitos.

Controlable de forma inalámbrica a través de un dispositivo inteligente (smartphones / tablets.) Visual e intuitiva app para smartphones / tablets. Disponible gratuitamente en Apple Store / Google Play. app CASAMBI

Forma automáticamente una rápida y segura red inalámbrica de malla con otras unidades eBLUE (hasta 127 unid / red).

Permite una programación horaria de escenas. Servicio en la nube.

El firmware del dispositivo puede ser actualizado en funcionamiento de manera inalámbrica. Sección máxima en clemas 0,75-1,5 mm2.

*BLUE MULTI4 is a Bluetooth controllable four channel PWM dimmer for constant voltage LED loads, such as LED strips and constant voltage LED modules.*

*eBLUE MULTI4 can control up to four channels. The maximum combined output current 6A which can be freely divided between 1-4 CH.*

*Very small size for easy installation.*

*Protected against overvoltage, overcurrent and short circuit situations.*

*Wirelessly controllably with a smart device (smartphone, tablet.) Intuitive and visual app for smartphones / tablets. Available for free on Apple Store / Google Play. CASAMBI*

*Forms automatically a fast and secure wireless mesh network with other eBLUE devices (up to 127 units / network).*


*Use timers to turn on and off scene at predefined times.*

*Cloud service that enhances user experience. Device firmware can be updated over the air. Max terminal section 0.75-1.5 mm2*

Características técnicas / Technical characteristics

Ref.	Tensiones de entrada y salida Input-output Voltage	Tipo de regulación Control signal	Intensidad máx. de salida Max output current	Potencia máx. de salida Max output powewr	Temp. máx. envolvente Max. temp at tc point	Temp. funcionamiento Operatin temp.	Control a través de Tipo Control made by
	Vdc	mA	A	12V 24V	tc (°)	ta (°)	
9953074	12-24	PWM	6	72 W 144 W	+75	-20...+45	DIM, TW, RGB, RGBW

Esquema de conexión / Connection diagram







URANO 150W 4000K

Campanas Led  
Ufo bays Led


Indoor



7420 60°




7421 90°




7422 120°


Luminous Intensity Distribution Curve




ILLUMINANCE at a Distance




Luminous Intensity Distribution Curve





ILLUMINANCE at a Distance




Luminous Intensity Distribution Curve



ILLUMINANCE at a Distance



REFERENCE	K	LED WATT	BEAM ANGLE	LUMENS	FINISH
7420	4000K	150W	60°	21000lm	Negro-Black
7421	4000K	150W	90°	21000lm	Negro-Black
7422	4000K	150W	120°	21000lm	Negro-Black
180-260V~ 50/60Hz CRI≥ 80					Aluminio-Aluminium








URANO 150W 5000K

Indoor

Campanas Led  
Ufo bays Led










REFERENCE	K	LED WATT	BEAM ANGLE	LUMENS	FINISH
7423	5000K	150W	60°	22500lm	Negro-Black
7424	5000K	150W	90°	22500lm	Negro-Black
7425	5000K	150W	120°	22500lm	Negro-Black
180-260V~ 50/60Hz CRI≥ 80					Aluminio-Aluminium





URANO 200W 4000K

Campanas Led  
Ufo bays Led




REFERENCE	K	LED WATT	BEAM ANGLE	LUMENS	FINISH
7426	4000K	200W	60°	28000lm	Negro-Black
7427	4000K	200W	90°	28000lm	Negro-Black
7428	4000K	200W	120°	28000lm	Negro-Black
180-260V~ 50/60Hz CRI≥ 80					Aluminio-Aluminium






URANO 200W 5000K

Campanas Led  
Ufo bays Led





7429 60°

Luminous Intensity Distribution Curve




Illuminance at a Distance





7430 90°

Luminous Intensity Distribution Curve




Illuminance at a Distance





7431 120°

Luminous Intensity Distribution Curve



Illuminance at a Distance






REFERENCE	K	LED WATT	BEAM ANGLE	LUMENS	FINISH
7429	5000K	200W	60°	30000lm	Negro-Black
7430	5000K	200W	90°	30000lm	Negro-Black
7431	5000K	200W	120°	30000lm	Negro-Black
180-260V~ 50/60Hz CRI≥ 80					Aluminio-Aluminium









	REFERENCE	K	LED WATT	LUMENS	FINISH
New	8152	3000K	6W	550lm	Blanco-White
New	8153	3000K	6W	550lm	Gris Oscuro-Dark grey
New	8154	3000K	6W	550lm	Negro-Black
	220-240V~ 50/60Hz CRI ≥80				Aluminio-Aluminium








	REFERENCE	K	LED WATT	LUMENS	FINISH
New	7990	3000K	20W	1900lm	Blanco-White
New	7991	3000K	20W	1900lm	Gris Oscuro-Dark grey
New	7992	3000K	20W	1900lm	Negro-Black
New	7993	3000K	20W	1900lm	Corten-Corten
New	7994	3000K	24W	2300lm	Blanco-White
New	7995	3000K	24W	2300lm	Gris Oscuro-Dark grey
New	7996	3000K	24W	2300lm	Negro-Black
New	7997	3000K	24W	2300lm	Corten-Corten
220-240V~ 50/60Hz CRI ≥80					Aluminio-Aluminium







REFERENCE	BULB (No incl)	FINISH
New 7929	2L x GU10	Gris Oscuro/madera-Dark Grey/wood
máx. 10W LED (No incl)	100-240V~ 50/60Hz	Aluminio/Cristal/Madera-Aluminium/Glass/SPC Wood



REFERENCE	BULB NO INCLUDED	FINISH
New 7928	1L x E27	Gris Oscuro/madera-Dark Grey/wood
máx. 15W LED (No incl)	100-240V~ 50/60Hz	Aluminio/PC/Madera-Aluminium/Opal PC/SPC Wood





REFERENCE	K	LED WATT	LUMENS	FINISH
6540	3000K	6W	620lm	Gris oscuro-Dark grey
6541	3000K	6W	620lm	Arena blanco-Sand white
New 7813	3000K	8W	830lm	Gris oscuro-Dark grey
New 7814	3000K	8W	830lm	Arena blanco-Sand white
220-240V~ 50/60Hz				Aluminio cristal-Aluminium glass



DRIVER  
TUV

LED life / LED vida  
30.000 h

ON / OFF  
30.000

5 años  
WARRANTY  
GARANTIA  
LED


LED  
INCLUDED

IP54






REFERENCE	K	LED WATT	LUMENS	FINISH
6850	3000K	10W	800lm	Gris + madera-Grey + wood
6851	3000K	12W	960lm	Gris + madera-Grey + wood
110-240V~ 50/60Hz CRI ≥80				Aluminio-Aluminium







REFERENCE	BULB NO INCLUDED	FINISH
7133	1L x E27	Beige oscuro-Dark beige
	máx. 20W LED (No incl)	100-240V ~ 50/60Hz
Aluminio/fibra textil sintética-Aluminium/synthetic textile fibre		



7131  
pág. 372










REFERENCE	BULB NO INCLUDED	FINISH
6551	1L x E27	Gris oscuro-Dark grey
6552	1L x E27	Gris oscuro-Dark grey
máx. 20W LED (No incl)		100-240V~ 50/60Hz Aluminio/cristal-Aluminium/glass








REFERENCE	K	LED WATT	LUMENS	FINISH	SENSOR	IP
6774	3000K	15W	1120lm	Gris Oscuro/Madera-Dark Grey/Wood	*	54
6770	3000K	13W	980lm	Gris Oscuro/Madera-Dark Grey/Wood		65
		100-240V~ 50/60Hz CRI:≥ 80		Aluminio/PC-Aluminium/PC		








6495



6494



REFERENCE	BULB NO INCLUDED	FINISH
6495	1L x E27	Grafito-Graphite
6494	1L x E27	Grafito-Graphite
máx. 20W LED (No incl)		100-240V~ 50/60Hz Aluminio/cristal-Aluminium/glass



7086  
pág. 340



7085  
pág. 406



6490  
pág. 408




6495






6492



6493




REFERENCE	BULB NO INCLUDED	FINISH
6492	2L x E27	Grafito-Graphite
6493	2L x E27	Grafito-Graphite
máx. 20W LED (No incl)		100-240V~ 50/60Hz Aluminio/cristal-Aluminium/glass







REFERENCE	BULB NO INCLUDED	FINISH
6508	1L x E27	Blanco-White
	máx. 20W LED (No incl)	100-240V~ 50/60Hz Polietileno-Polyethylene







VOLCANO

Apliques exterior-Outdoor wall lights

Outdoor

IP65



REFERENCE	BULB NO INCLUDED	FINISH
6482	2L x E27	Grafito-Graphite
6483	1L x E27	Grafito-Graphite
máx. 20W LED (No incl)		100-240V~ 50/60Hz Aluminio/cristal-Aluminium/glass





7908  
pág. 360







REFERENCE	BULB (No incl)	FINISH
6558	1L x GX53	Gris oscuro-Dark grey
6559	1L x GX53	Blanco-White
máx. 10W LED (No incl)		100-240V~50/60Hz Aluminio-Aluminium



Bombillas recomendadas-Suggested bulbs

REFERENCE	Wattios LED	CCT	Lumens	Ángulo luz
R09224	9W	3000K	730lm	120°
R09225	9W	4000K	740lm	120°






OAMI 005818614-0003




Luz orientable-Orientable light





REFERENCE	BULB (No incl)	FINISH
6769	2L x GX53	Gris oscuro-Dark grey
6768	2L x GX53	Blanco-White
máx. 10W LED (No incl)		100-240V~50/60Hz Aluminio-Aluminium




Bombillas recomendadas-Suggested bulbs


REFERENCE	Wattios LED	CCT	Lumens	Ángulo luz
R09224	9 W	3000K	730lm	120°
R09225	9 W	4000K	740lm	120°








REFERENCE	BULB (No incl)	FINISH
7470	2L x GU10	Corten-Corten
7471	2L x GU10	Corten-Corten
7472	1L x GU10	Corten-Corten
7473	1L x GU10	Corten-Corten
máx. 10W LED (No incl)		100-240V ~ 50/60Hz Aluminio/Cristal- Aluminium/Glass



Bombillas recomendadas-Suggested bulbs

K	Wat LED	On/Off	Dimmable	Lumens
2700K	7W	R09254	R09257	510lm
3000K	7W	R09255	R09258	540lm
4000K	7W	R09256	R09259	570lm






6510



6511



7037




6514



6515



7038



REFERENCE	BULB (No incl)	FINISH
6510	2L x GU10	Gris oscuro-Dark grey
6511	2L x GU10	Blanco-White
7037	2L x GU10	Negro-Black
6514	2L x GU10	Gris oscuro-Dark grey
6515	2L x GU10	Blanco-White
7038	2L x GU10	Negro-Black
máx. 10W LED (No incl)		100-240V~50/60Hz Aluminio/Cristal- Aluminium/Glass



Bombillas recomendadas-Suggested bulbs

K	Wat LED	On/Off	Dimmable	Lumens
2700K	7W	R09254	R09257	510lm
3000K	7W	R09255	R09258	540lm
4000K	7W	R09256	R09259	570lm




7039



6513



6512




7040



6517








6516







REFERENCE	BULB (No incl)	FINISH
6512	1L x GU10	Gris oscuro-Dark grey
6513	1L x GU10	Blanco-White
7039	1L x GU10	Negro-Black
6516	1L x GU10	Gris oscuro-Dark grey
6517	1L x GU10	Blanco-White
7040	1L x GU10	Negro-Black
máx. 10W LED (No incl)		100-240V~50/60Hz Aluminio/Cristal- Aluminium/Glass








REFERENCE	K	LED WATT	LUMENS	FINISH
6520	3000K	12W	1100lm	Gris oscuro-Dark grey
6521	3000K	12W	1100lm	Blanco arena-Sand white
6524	3000K	12W	1100lm	Negro arena-Sand black
6527	3000K	12W	1100lm	Corten-Corten
6522	3000K	12W	1100lm	Gris oscuro-Dark grey
6523	3000K	12W	1100lm	Blanco arena-Sand white
110-240V~ 50/60Hz CRI ≥80				Aluminio-Aluminium





REFERENCE	K	LED WATT	LUMENS	FINISH
7647	4000K	12W	1100lm	Gris oscuro-Dark grey
7648	4000K	12W	1100lm	Blanco arena-Sand white
7649	4000K	12W	1100lm	Negro arena-Sand black
7650	4000K	12W	1100lm	Corten-Corten
7645	4000K	12W	1100lm	Gris oscuro-Dark grey
7646	4000K	12W	1100lm	Blanco arena-Sand white
220-240V~ 50/60Hz CRI ≥80				Aluminio-Aluminium







DAVOS XL

Apliques exterior-Outdoor wall lights

Outdoor




REFERENCE	K	LED WATT	LUMENS	FINISH
7435	3000K	20W	1830lm	Gris oscuro-Dark grey
7436	3000K	20W	1830lm	Blanco arena-Sand white
7437	3000K	20W	1830lm	Negro arena-Sand black
7438	3000K	20W	1830lm	Corten-Corten
7651	4000K	20W	1830lm	Gris oscuro-Dark grey
7652	4000K	20W	1830lm	Blanco arena-Sand white
7653	4000K	20W	1830lm	Negro arena-Sand black
7654	4000K	20W	1830lm	Corten-Corten
220-240V ~ 50/60Hz CRI ≥ 80				Aluminio-Aluminium






DAVOS DOUBLE 24W

Apliques exterior-Outdoor wall lights


Outdoor



	REFERENCE	K	LED WATT	LUMENS	FINISH
New	7815	3000K	4×6 W	2200lm	Gris oscuro-Dark grey
New	7816	3000K	4×6 W	2200lm	Blanco arena-Sand white
New	7817	3000K	4×6 W	2200lm	Negro arena-Sand black
New	7818	3000K	4×6 W	2200lm	Corten-Corten
New	7819	4000K	4×6 W	2200lm	Gris oscuro-Dark grey
New	7820	4000K	4×6 W	2200lm	Blanco arena-Sand white
New	7821	4000K	4×6 W	2200lm	Negro arena-Sand black
New	7822	4000K	4×6 W	2200lm	Corten-Corten
			220-240V~ 50/60Hz		Aluminio-Aluminium










REFERENCE	K	LED WATT	LUMENS	FINISH
6525	3000K	8W	750m	Gris oscuro-Dark grey
6526	3000K	8W	750m	Blanco arena-Sand white
220-240V~ 5 0/60Hz CRI ≥80				Aluminio-Aluminium







REFERENCE	K	LED WATT	LUMENS	FINISH
6530	3000K	6 W	660lm	Gris oscuro-Dark grey
6531	3000K	6 W	660lm	Blanco arena-Sand white
220-240V ~ 5 0/60Hz CRI ≥80				Aluminio-Aluminium








REFERENCE	K	LED WATT	LUMENS	FINISH	
6534	3000K	9.6W	720lm	Gris oscuro-Dark grey	ø 150
6535	3000K	9.6W	720lm	Blanco-White	ø 150
6538	3000K	9.6W	720lm	Corten-Corten	ø 150
6536	3000K	9.6W	720lm	Gris oscuro-Dark grey	150 x 150
6537	3000K	9.6W	720lm	Blanco-White	150 x 150
6539	3000K	9.6W	720lm	Corten-Corten	150 x 150
220-240V~ 50/60Hz				Aluminio-Aluminium	

IP54







REFERENCE	BULB NO INCLUDED	FINISH
7050	1L x E27	Gris Oscuro-Dark Grey
7051	1L x E27	Blanco-White
7052	1L x E27	Corten-Corten
máx. 20W LED (No incl)		100-240V ~ 50/60Hz Aluminio-Aluminium








Outdoor



IP54



PIR sensor  
A:120°  
D:≤6m



Charge: 6-8h (Sunshine)  
Work time : Full light 3h / Micro light 25h



6495  
pág. 308




7085  
pág. 406



6490  
pág. 408


REFERENCE	K	LED WATT	LUMENS	FINISH
7086	3000K	2,2W	188lm	Grafito-Graphite
DC 3.7V CRI≥ 80				Aluminio-Aluminium








PIR sensor  
A:180°  
D:≤6m




Charge: 6-8h (Sunshine)  
Work time :Full light 3h / Micro light 25h



REFERENCE	K	LED WATT	LUMENS	FINISH
7098	3000K	2,2W	188lm	Grafito-Graphite
DC 3.7V CRI≥ 80			Aluminio-Aluminium	








REFERENCE	K	LED WATT	LUMENS	FINISH
7072	3000K	9 W	762lm	Gris oscuro-Dark grey
7073	3000K	9 W	762lm	Blanco-White
		100-240V~ 50/60Hz CRI≥ 80		Aluminio/PC-Aluminium/PC



DRIVER  
TUV



REFERENCE	K	LED WATT	LUMENS	FINISH
7070	3000K	9 W	773lm	Gris oscuro-Dark grey
7071	3000K	9 W	773lm	Blanco-White
		100-240V~ 50/60Hz CRI≥ 80		Aluminio/PC-Aluminium/PC






REFERENCE	K	LED WATT	LUMENS	FINISH
7045	3000K	6 W	510lm	Gris oscuro-Dark grey
7046	3000K	6 W	510lm	Blanco-White
220-240V~ 50/60Hz CRI≥ 80				Aluminio/PC-Aluminium/PC



8151  
pág. 416







REFERENCE	K	LED WATT	LUMENS	FINISH
7062	3000K	9W	725lm	Gris oscuro-Dark grey
7063	3000K	9W	725lm	Blanco-White
220-240V~ 50/60Hz CRI≥ 80				Aluminio/PC-Aluminium/PC



7060  
pág. 366





IP65



DRIVER  
TÜV






REFERENCE	K	LED WATT	LUMENS	FINISH
7108	3000K	12W	1100lm	Gris Piedra-Stone Grey
7109	3000K	12W	1100lm	Blanco-White
		220-240V~ 50/60Hz		Cemento liso-Smooth cement



7501  
pág. 420






REFERENCE	BULB NO INCLUDED	FINISH
7182	2L x GU10	Blanco-White
7183	2L x GU10	Gris oscuro-Dark grey
máx. 12W LED (No incl)		100-240V~ 50/60Hz Hormigón-Concrete





7187  
pág. 370



REFERENCE	BULB NO INCLUDED	FINISH
7180	2L x GU10	Blanco-White
7181	2L x GU10	Gris oscuro-Dark grey
máx. 12W LED (No incl)		100-240V~ 50/60Hz Hormigón-Concrete






REFERENCE	K	LED WATT	LUMENS	FINISH
6542	3000K	6 W	420lm	Gris oscuro-Dark grey
6543	3000K	6 W	420lm	Blanco arenado-Sand white
220-240V~ 50/60Hz				Aluminio-Aluminium









REFERENCE	K	LED WATT	LUMENS	FINISH
6470	3000K	10W	700lm	Gris oscuro-Dark grey
		100-240V ~ 50/60Hz	Aluminio /PC- Aluminium/PC	



6496



6497



REFERENCE	K	LED WATT	LUMENS	FINISH
6496	3000K	10W	700lm	Gris oscuro-Dark grey
6497	3000K	10W	700lm	Gris oscuro-Dark grey
		100-240V ~ 50/60Hz	Aluminio /PC- Aluminium/PC	



6498  
pág. 422


KANDANCHÚ

Plafón exterior-Outdoor ceiling lamp

Outdoor





REFERENCE		BULB NO INCLUDED	FINISH
New	7900	GU10	Blanco-White
New	7901	GU10	Gris oscuro-Dark grey
New	7902	GU10	Negro-Black
New	7903	GU10	Corten-Corten
		1x GU10 máx.10W	100-240V ~ 50/60Hz Aluminio/Cristal-Aluminium/Glass



Plafón exterior-Ceiling lamp outdoor



REFERENCE		BULB NO INCLUDED	FINISH
New	7904	GU10	Blanco-White
New	7905	GU10	Gris oscuro-Dark grey
New	7906	GU10	Negro-Black
New	7907	GU10	Corten-Corten
		1x GU10 máx.10W	100-240V ~ 50/60Hz Aluminio/Cristal-Aluminium/Glass




Bombillas recomendadas-Suggested bulbs


K	Wat LED	On/Off	Dimmable	Lumens
2700K	7W	R09254	R09257	510lm
3000K	7W	R09255	R09258	540lm
4000K	7W	R09256	R09259	570lm







	REFERENCE	BULB NO INCLUDED	FINISH
New	7908	E27	Gris Oscuro-Dark Grey
		1x E27 máx.20W	100-240V~ 50/60Hz Aluminio/Cristal-Aluminium/Glass



Bombillas recomendadas-Suggested bulbs


	REFERENCE	Wattios LED	CCT	Lumens	Ángulo luz
	R09133	10W	3000K	1050lm	320°
	R09215	10W	4000K	1080lm	320°
	R09134	10W	5000K	1100lm	320°
	R09139	14W	3000K	1460lm	240°
	R09140	14W	4000K	1510lm	240°








6553



6554



REFERENCE	BULB NO INCLUDED	FINISH
6553	1L x E27	Gris oscuro-Dark grey
6554	1L x E27	Gris oscuro-Dark grey
máx. 20W LED (No incl)		100-240V~ 50/60Hz Aluminio/cristal-Aluminium/glass



6550  
pág. 410

6555  
pág. 382

6551  
pág. 304








7065




7066



REFERENCE	BULB NO INCLUDED	FINISH
7065	2L x E27	Gris oscuro-Dark grey
7066	2L x E27	Gris oscuro-Dark grey
máx. 20W LED (No incl)		100-240V ~ 50/60Hz Aluminio/cristal-Aluminium/glass








REFERENCE	K	LED WATT	LUMENS	FINISH
7060	3000K	9W	725lm	Gris oscuro-Dark grey
7061	3000K	9W	725lm	Blanco-White
			220-240V~ 50/60Hz	Aluminio/PC-Aluminium/PC



7062  
pág. 348








REFERENCE	K	LED WATT	LUMENS	FINISH
7055	3000K	14W	1180lm	Gris oscuro-Dark grey
7056	3000K	14W	1180lm	Blanco-White
100-240V~ 50/60Hz CRI≥ 80				Aluminio/Cristal-Aluminium/Glass








REFERENCE	BULB NO INCLUDED	FINISH
7184	1L x GU10	Blanco-White
7185	1L x GU10	Gris oscuro-Dark grey
máx. 12W LED (No incl)		100-240V~ 50/60Hz Hormigón-Concrete



7181  
pág. 352



IP65



REFERENCE	BULB NO INCLUDED	FINISH
7186	1L x GU10	Blanco-White
7187	1L x GU10	Gris oscuro-Dark grey
máx. 12W LED (No incl)		100-240V~ 50/60Hz Hormigón-Concrete





POLINESIA  
By Santiago Sevillano

Colgantes exterior-Outdoor pendant lamp



REFERENCE	BULB NO INCLUDED	FINISH
7131	1L x E27	Beige oscuro-Dark beige
máx. 20W LED (No incl) 100-240V~ 50/60Hz Aluminio/fibra textil sintética-Aluminium/synthetic textile fibre		



IP44




Registered N° 007663331-0007



POLINESIA  
By Santiago Sevillano

Colgantes exterior-Outdoor pendant lamp



7133  
pág. 302

REFERENCE	BULB NOT INCLUDED	FINISH
7130	1L x E27	Beige oscuro-Dark beige
máx. 20W LED (No incl) 100-240V~ 50/60Hz Aluminio/fibra textil sintética-Aluminium/synthetic textile fibre		




IP44



KINKÉ  
By Santolaria & Lluscà

Colgantes exterior-Outdoor pendant lamp



REFERENCE	BULB NO INCLUDED	FINISH
6212	1L x E27	Blanco/Gris antracita-White/Gray Anthracite
	máx. 20W LED (No incl)	100-240V~ 50/60Hz ABS/PE/Aluminium

OAMI 004721413-023 / 024 / 025




IP44



KINKÉ  
Santolaria & Lluscà

Colgantes exterior-Outdoor pendant lamp




REFERENCE	BULB NO INCLUDED	FINISH
6211	1L x E27	Blanco/Gris antracita-White/Gray Anthracite
	máx. 20W LED (No incl)	100-240V~ 50/60Hz ABS/PE/Aluminium






KINKÉ  
Santolaria & Llusçà

Colgantes & Portàtil exterior-Outdoor pendant lamp & Portable



REFERENCE	BULB NO INCLUDED	FINISH
6213	1L x E27	Blanco/Gris antracita-White/Gray Anthracite
	máx. 20W LED (No incl)	100-240V~ 50/60Hz ABS/PE/Aluminium




6215



6218



6214




REFERENCE	FINISH	
6215	Peana-Base	Gris antracita/Gray Anthracite
6214	Gancho-Hook	Gris antracita/Gray Anthracite
6218	Peana-Base	Acero Inoxidable-Base mármol negro Stainless Steel-Black marble base

OAMI 004721413-023 / 024 / 025







6553  
pág. 362


6550  
pág. 410

6551  
pág. 304

REFERENCE	BULB NO INCLUDED	FINISH
6555	1L × E27	Gris oscuro-Dark grey
	máx. 20W LED (No incl)	100-240V ~ 50/60Hz Aluminio/cristal-Aluminium/glass










IP44

REFERENCE	BULB NO INCLUDED	FINISH	
1397	1L x E27	Blanco-White	ø350
1398	1L x E27	Blanco-White	ø400
1399	1L x E27	Blanco-White	ø500
máx. 20W LED (No incl)		PE / ABS / Aluminio-PE / ABS / Aluminium	





1388  
pág. 428








	REFERENCE	K	LED WATT	LUMENS	FINISH
New	7930	3000K	2W	180lm	Blanco-White
New	7931	3000K	2W	180lm	Negro-Black
New	7932	3000K	2W	180lm	Corten-Corten
			DC 5V / 1A		Aluminio-Aluminium







	REFERENCE	K	LED WATT	LUMENS	FINISH
New	7933	3000K	2W	180lm	Blanco-White
New	7934	3000K	2W	180lm	Negro-Black
New	7935	3000K	2W	180lm	Corten-Corten
			DC 5V / 1A		Aluminio-Aluminium







REFERENCE	K	LED WATT	LUMENS	FINISH
7988	3000K	2W	230lm	Blanco-White
7989	3000K	2W	230lm	Negro-Black
		DC 5V/1A CRI≥ 80		Aluminio-PC-Aluminum/PC







REFERENCE	K	LED WATT	LUMENS	FINISH
7985	3000K	2W	180lm	Blanco-White
7986	3000K	2W	180lm	Negro-Black
7987	3000K	2W	180lm	Corten-Corten
DC 5V/1A CRI≥ 80				Aluminio-Aluminum







REFERENCE	K	LED WATT	LUMENS	FINISH
7116	3000K	2W	155lm	Blanco-White
7115	3000K	2W	155lm	Negro-Black
		DC 5V/1A CRI≥ 85		Aluminio/PC-Aluminum/PC




IP54







REFERENCE	K	LED WATT	LUMENS	FINISH
6480	3000K	2.2W	188lm	Negro mate-Matt black
6484	3000K	2.2W	188lm	Amarillo-Yellow
6481	3000K	2.2W	188lm	Blanco mate-Matt white
DC 5V/1A CRI≥ 85				Aluminio/PC-Aluminum/PC







REFERENCE	K	LED WATT	LUMENS	FINISH
7100	3000K	2.2W	188lm	Blanco mate-Matt white
7101	3000K	2.2W	188lm	Negro mate-Matt black
		DC 3.7V CRI≥ 80		Aluminio/PC-Aluminum/PC



6480  
pág. 396





IP54







REFERENCE	K	LED WATT	LUMENS	FINISH	SIZES
7090	3000K	3W	238lm	Grafito-Graphite	290×175mm
7091	3000K	3W	238lm	Blanco-White	290×175mm
7092	3000K	3W	238lm	Grafito-Graphite	360×175mm
7093	3000K	3W	238lm	Blanco-White	360×175mm
		DC 3.7V CRI≥ 80		Aluminio-Aluminum	



Charge: 16 ~17H (sunshine)  
6 ~7H (usbcharging)



IP54







REFERENCE	K	LED WATT	LUMENS	FINISH	SIZES
6491	3000K	2,2W	188lm	Grafito-Graphite	470mm
6905	3000K	2,2W	188lm	Blanco-White	470mm
6907	3000K	2,2W	188lm	Grafito-Graphite	670mm
6906	3000K	2,2W	188lm	Blanco-White	670mm
DC 5V/1A CRI≥ 80				Aluminio-Aluminum	



IP54




FLAME

by Santiago Sevillano Studio

Lámpara de suelo-Floor lamp

Outdoor




REFERENCE	BULB NO INCLUDED	FINISH
1326	1L x E27	Blanco-White
	máx. 20W LED (No incl)	100-240V~ 50/60Hz PE/ABS-PE/ABS

Complementos Exterior-Outdoor Complements		
Piqueta-Spike 210 mm	Piqueta-Spike 160 mm	Base-Ground base ø50
TU0652	TU0492	TU0494




1400  
pág. 432



IP65


FLAME









PIR sensor  
A:120°  
D:≤6m




Charge: 6-8h (Sunshine)  
Work time : Full light 3h / Micro light 25h




7086      6495  
pág. 340      pág. 308




Included




Included



REFERENCE	K	LED WATT	LUMENS	FINISH
7085	3000K	3,5W	300lm	Grafito-Graphite
		DC 3.7V CRI≥ 80		Aluminio-Aluminum








REFERENCE	BULB NO INCLUDED	FINISH
6490	1L x E27	Grafito-Graphite
	máx. 20W LED (No incl)	100-240V~ 50/60Hz Aluminio/cristal-Aluminium/glass



6492  
pág. 308







REFERENCE	BULB NO INCLUDED	FINISH
6550	1L x E27	Gris oscuro-Dark grey
	máx. 20W LED (No incl)	100-240V ~ 50/60Hz Aluminio/cristal-Aluminium/glass



6553  
pág. 362

6555  
pág. 382

6551  
pág. 304








REFERENCE	K	LED WATT	LUMENS	FINISH	HEIGHT
6771	3000K	13W	980lm	Gris Oscuro/Madera-Dark Grey/Wood	350
6772	3000K	13W	980lm	Gris Oscuro/Madera-Dark Grey/Wood	600
6773	3000K	13W	980lm	Gris Oscuro/Madera-Dark Grey/Wood	1000
		100-240V~ 50/60Hz CRI:≥ 80		Aluminio/PC-Aluminium/PC	



6770  
 pág. 306








PIR sensor  
A:120°  
D:≤6m





Charge: 6-8h (Sunshine)  
Work time : Full light 3h / Micro light 25h



Included




Included



REFERENCE	K	LED WATT	LUMENS	FINISH
7088	3000K	2,2W	188lm	Grafito-Graphite
DC 3.7V CRI≥ 80			Aluminio-Aluminium	







7045  
pág. 346

REFERENCE	K	LED WATT	LUMENS	FINISH
8151	3000K	12W	1020lm	Gris oscuro-Dark grey
		220-240V~ 50/60Hz CRI:≥ 80		Aluminio/PC-Aluminium/PC








REFERENCE	BULB NO INCLUDED	FINISH
8108	1L x E27	Gris Oscuro-Dark grey
8109	1L x E27	Gris Oscuro-Dark grey
	máx. 20W LED (No incl)	100-240V ~ 50/60Hz Aluminium/PC-Aluminium/PC







REFERENCE	K	LED WATT	LUMENS	FINISH
7105	3000K	6.5W	490lm	Gris Piedra-Stone grey
7106	3000K	12W	905lm	Gris Piedra-Stone grey
220-240V~ 50/60Hz CRI:≥ 80			Cemento liso-Smooth cement	



7108  
pág. 350







REFERENCE	K	LED WATT	LUMENS	FINISH	SIZES
6498	3000K	10W	700lm	Gris oscuro-Dark grey	600
6499	3000K	10W	700lm	Gris oscuro-Dark grey	1000
100-240V ~ 50/60Hz CRI:≥ 80				Aluminio /PC- Aluminium/PC	



6497  
pág. 357

LED life / LED vida

30.000 h

ON / OFF

30.000

LED

INCLUDED

garantía fabricante 5 años

WARRANTY 5 YEARS

GARANTÍA 5 AÑOS


LED

IP54





REFERENCE	BULB NO INCLUDED	FINISH
8155	1L x GU10	Negro-Black
	máx. 12W LED (No incl)	100-240V ~ 50/60Hz Aluminio-Aluminium




Bombillas recomendadas-Suggested bulbs

K	Wat LED	On/Off	Phase cut	Lumens
2700K	7W	R09254	R09257	510lm
3000K	7W	R09255	R09258	540lm
4000K	7W	R09256	R09259	570lm








REFERENCE	BULB NO INCLUDED		FINISH
7107	1L x GU10		Gris Piedra-Stone Grey
	máx. 12W LED (No incl)	100-240V ~ 50/60Hz	Cemento liso-Smooth cement



7108  
pág. 350






Bombillas recomendadas-Suggested bulbs				
K	Wat LED	On/Off	Phase cut	Lumens
2700K	7W	R09254	R09257	510lm
3000K	7W	R09255	R09258	540lm
4000K	7W	R09256	R09259	570lm







REFERENCE	BULB NO INCLUDED	FINISH	
1388	1L x E27	Blanco-White	ø350
1391	1L x E27	Blanco-White	ø400
1394	1L x E27	Blanco-White	ø500
máx. 20W LED (No incl)		100-240V~ 50/60Hz PE/ABS-PE/ABS	



Complementos exterior \*NO INCLUIDO-Outdoor complements \*NOT INCLUDED

TU0492	TU0652	TU0653	TU0494



1397  
pág. 384





ESPIGA  
by Santolaria & Lluscà


Lámpara de suelo-Floor lamp

Outdoor



REFERENCE	BULB NO INCLUDED	FINISH
6545	2L × G9	Gris oscuro-Dark Grey
6546	3L × G9	Gris oscuro-Dark Grey
6547	5L × G9	Gris oscuro-Dark Grey
máx. 5W LED (No incl)		100-240V~ 50/60Hz Aluminio-Aluminium

Complementos exterior \*NO INCLUIDO-Outdoor complements \*NOT INCLUDED



OAMI 005818614-0001



FLAME  
by Santiago Sevillano Studio

Lámpara de suelo-Floor lamp


Outdoor



OAMI 01793845-0001



REFERENCE	BULB NO INCLUDED	FINISH
1400	4L x GU10 máx 12W LED (No incl)	Blanco-White
	1L x E27 máx 20W LED (No incl)	
	100-240V~ 50/60Hz	PE/Acero-PE/Steel



Bombillas recomendadas-Suggested bulbs

BULB	Reference	Reference
GU10	R09219	R09220
E27	R09139	R09140

Complementos exterior \*NO INCLUIDO-Outdoor complements \*NOT INCLUDED

TU0652	TU0653	TU0494



1326  
pág. 404









REFERENCE	K	LED WATT	LUMENS	FINISH
7011	3000K	3W	210lm	Gris Oscuro-Dark Grey
7012	3000K	3W	210lm	Blanco arena-Sand white
7640	3000K	3W	210lm	Corten-Corten
7015	3000K	6W	420lm	Gris Oscuro-Dark Grey
7016	3000K	6W	420lm	Blanco arena-Sand white
7642	3000K	6W	420lm	Corten-Corten
220-240V~ 50/60Hz CRI:≥ 80				Aluminio/PC-Aluminium/PC



7015







REFERENCE	K	LED WATT	LUMENS	FINISH
7013	3000K	3W	210lm	Gris Oscuro-Dark Grey
7014	3000K	3W	210lm	Blanco arena-Sand white
7641	3000K	3W	210lm	Corten-Corten
7017	3000K	6W	420lm	Gris Oscuro-Dark Grey
7018	3000K	6W	420lm	Blanco arena-Sand white
7643	3000K	6W	420lm	Corten-Corten
220-240V~ 50/60Hz CRI:≥ 80				Aluminio/PC-Aluminium/PC







ASPEN



Señalizadores empotrables-Recessed step wall lights

Outdoor





REFERENCE	K	LED WATT	LUMENS	FINISH	HEIGHT
7021	3000K	3W	210lm	Gris Oscuro-Dark Grey	ø80
7022	3000K	3W	210lm	Negro arena-Sand black	ø80
7023	3000K	3W	210lm	Blanco arena-Sand white	ø80
7024	3000K	3W	210lm	Gris Oscuro-Dark Grey	80 × 80
7025	3000K	3W	210lm	Negro arena-Sand black	80 × 80
7026	3000K	3W	210lm	Blanco arena-Sand white	80 × 80
200-240V~ 50/60Hz CRI:≥ 80				Aluminio/PC-Aluminium/PC	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Modos Instalación-Installation Forms



Con tubo carcasa-Recessed tube housing



76mm




Con pinzas-With clamps




74mm








REFERENCE	K	LED WATT	LUMENS	FINISH	HEIGHT
7027	3000K	3W	210lm	Gris Oscuro-Dark Grey	ø80
7028	3000K	3W	210lm	Negro arena-Sand black	ø80
7029	3000K	3W	210lm	Blanco arena-Sand white	ø80
7030	3000K	3W	210lm	Gris Oscuro-Dark Grey	80 × 80
7031	3000K	3W	210lm	Negro arena-Sand black	80 × 80
7032	3000K	3W	210lm	Blanco arena-Sand white	80 × 80
200-240V~ 50/60Hz CRI:≥ 80				Aluminio/PC-Aluminium/PC	



• Modos Instalación-Installation Forms



Con tubo carcasa-Recessed tube housing

76mm



Con pinzas-With clamps

74mm



LED life / LED vida

30.000 h



ON / OFF

30.000



garantía.mantraco 5 años

WARRANTY

GARANTIA

LED



LED

INCLUDED





IP65





CONEXIÓN IP 68

Outdoor

TÜV

REFERENCE	OPERATING RATING	VOLTAGE	AMPERE	WIRE SECTION	OUTER CABLE DIAMETER	IP
TU0662	-40°C + 105C	400V AC	17,5A	0.5 mm <sup>2</sup> - 1,5 mm <sup>2</sup>	3,5 mm-7,0mm; 7mm-10mm	68
TU0663	-40°C + 105C	400V AC	24A	0.5 mm <sup>2</sup> - 2,5 mm <sup>2</sup>	5 mm-9mm; 9mm-12mm	68
PC-PC PA66 Nylon						

TU0662




TU0663



PIQUETAS

Complementos exterior-*Outdoor complements*

REFERENCE	DESCRIPCIÓN	ACABADO	TAMAÑO
TU0492	Piqueta 16cm	Negro-Black	40×160 mm
TU0652	Piqueta 21cm	Negro-Black	45×210 mm
TU0653	Piqueta 26cm	Negro-Black	55×270 mm
TU0494	Disco para suelo	Negro-Black	ø50 mm
Aluminio-Aluminium			



Base sujeción/Fixing base

TU0494






LED G9 Bulb

- Características**
- \* Voltaje:AC 220-240V 50/60Hz 12mA
  - \* 20,000 hrs. vida útil
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 25W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion


- Features**
- \* Voltage: AC 220-240V 50/60Hz 12mA
  - \* 20,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 25W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



2.5W G9 230 Lumen




Item No.	R09184	R09185
Potencia nominal/Wattage(W)	2.5	
Temperatura de color/CCT(K)	2700K	5000K
Flujo luminoso/Luminous Flux(lm)	220	230
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz	
Regulable/Dimmable	YES	
CRI	≥80	
Casquillo/Lamp Head	G9	
Angulo/Beam Angle(deg)	360°	
Material	PC	
Dimensiones/Dimensions(mm)	Φ16*48	



LED G9 Bulb

- Características**
- \* Voltaje:AC 220-240V 50/60Hz 10mA
  - \* 20,000 hrs. vida útil
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 30W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion


- Features**
- \* Voltage: AC 220-240V 50Hz 10mA
  - \* 20,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 30W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



2.5W G9 250 Lumen




Item No.	R09226	R09227
Potencia nominal/Wattage(W)	2.5	
Temperatura de color/CCT(K)	3000K	4000K
Flujo luminoso/Luminous Flux(lm)	240	250
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz	
Regulable/Dimmable	NO	
CRI	≥80	
Casquillo/Lamp Head	G9	
Angulo/Beam Angle(deg)	360°	
Material	Cristal / Glass	
Dimensiones/Dimensions(mm)	Φ14*48	



LED G9 Bulb

- Características**
- \* Voltaje:AC 220-240V 50/60Hz 25mA
  - \* 20,000 hrs. vida útil
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 30W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion


- Features**
- \* Voltage: AC 220-240V 50/60Hz 25mA
  - \* 20,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 30W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



3W G9 268 Lumen




Item No.	R09182
Potencia nominal/Wattage(W)	3
Temperatura de color/CCT(K)	2700K
Flujo luminoso/Luminous Flux(lm)	268
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz
Regulable/Dimmable	NO
CRI	≥80
Casquillo/Lamp Head	G9
Angulo/Beam Angle(deg)	360°
Material	Ceramic / PC
Dimensiones/Dimensions(mm)	Φ19*50



LED G9 Bulb

- Características**
- \* Voltaje:AC 220-240V 50/60Hz 30mA
  - \* 20,000 hrs. vida útil
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 30W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion


- Features**
- \* Voltage: AC 220-240V 50/60Hz 30mA
  - \* 20,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 30W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



3.5W G9 375 Lumen



Item No.	R09202	R09203
Potencia nominal/Wattage(W)	3.5	
Temperatura de color/CCT(K)	2700K	5000K
Flujo luminoso/Luminous Flux(lm)	360	375
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz	
Regulable/Dimmable	NO	
CRI	≥80	
Casquillo/Lamp Head	G9	
Angulo/Beam Angle(deg)	360°	
Material	Ceramic / PCB	
Dimensiones/Dimensions(mm)	Φ16*50	







LED G4 Bulb

- Características**
- \* Voltaje:AC/DC 12V 140mA
  - \* 20,000 hrs. vida util
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 20W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion


- Features**
- \* Voltage: AC/DC 12V 140mA
  - \* 20,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 20W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



2W G4 190 Lumen




Item No.	R09209	R09210
Potencia nominal/Wattage(W)	2	
Temperatura de color/CCT(K)	3000K	5000K
Flujo luminoso/Luminous Flux(lm)	190	
Tension nominal/Voltage(V)	AC/DC 12V	
Regulable/Dimmable	NO	
CRI	≥80	
Casquillo/Lamp Head	G4	
Angulo/Beam Angle(deg)	240°	
Material	PC	
Dimensiones/Dimensions(mm)	L16*W12*H45	




LED G4 Bulb

- Características**
- \* Voltaje:AC/DC 12V 345mA
  - \* 20,000 hrs. vida util
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 35W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion


- Features**
- \* Voltage: AC/DC 12V 345mA
  - \* 20,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 35W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



5W G4 500 Lumen




Item No.	R09243	R09247
Potencia nominal/Wattage(W)	5	
Temperatura de color/CCT(K)	3000K	4000K
Flujo luminoso/Luminous Flux(lm)	500	
Tension nominal/Voltage (V)	AC/DC 12V	
Regulable/Dimmable	NO	
CRI	≥80	
Casquillo/Lamp Head	G4	
Angulo/Beam Angle(deg)	360°	
Material	PCB&Ceramic	
Dimensiones/Dimensions(mm)	Φ19*57	




LED GU10 Bulb

- Características**
- \* 15,000 hrs. vida util
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 75W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion


- Features**
- \* 15,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 75W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



Dimmable  
9W GU10 820 Lumen




Item No.	R09218	R09219	R09220
Potencia nominal/Wattage(W)	9		
Temperatura de color/CCT(K)	3000K	3000K	4000K
Flujo luminoso/Luminous Flux(lm)	800	800	820
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz		
Regulable/Dimmable	YES	NO	NO
CRI	≥80		
Casquillo/Lamp Head	GU10		
Angulo/Beam Angle(deg)	50°		
Material	Aluminio+PC/Aluminum+PC		
Dimensiones/Dimensions(mm)	Φ50*74		



LED GU10 Bulb

- Características**
- \* Voltaje:AC 220-240V 50/60Hz 40mA
  - \* 15,000 hrs. vida util
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 35W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion


- Features**
- \* Voltage: AC 220-240V 50/60Hz 40mA
  - \* 15,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 35W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



4W GU10 360 Lumen



Item No.	R09207
Potencia nominal/Wattage(W)	4
Temperatura de color/CCT(K)	3000K
Flujo luminoso/Luminous Flux(lm)	360
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz
Regulable/Dimmable	NO
CRI	≥80
Casquillo/Lamp Head	GU10
Angulo/Beam Angle(deg)	360°
Material	Aluminio+PC/Aluminum+PC
Dimensiones/Dimensions(mm)	Φ29*81






LED GU10 Bulb


- Caracteristicas**
- \* Voltaje:AC 220-240V 50/60Hz 60mA
  - \* 15,000 hrs. vida util
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 80W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion

- Features**
- \* Voltage: AC 220-240V 50/60Hz 60mA
  - \* 15,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 80W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



8W GU10 641 Lumen

Item No.	R09156	R09157
Potencia nominal/Wattage(W)	8	
Temperatura de color/CCT(K)	3000K	5000K
Flujo luminoso/Luminous Flux(lm)	641	
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz	
Regulable/Dimmable	NO	
CRI	≥80	
Casquillo/Lamp Head	GU10	
Angulo/Beam Angle(deg)	60°	
Material	Aluminio&PC / Aluminum&PC	
Dimensiones/Dimensions(mm)	Φ50*58	



LED GU10 Bulb


- Caracteristicas**
- \* Voltaje:AC 220-240V 50/60Hz 55mA
  - \* 15,000 hrs. vida util
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 60W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion

- Features**
- \* Voltage: AC 220-240V 50/60Hz 55mA
  - \* 15,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 60W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



6W GU10 540 Lumen


Item No.	R09196	R09214	R09197
Potencia nominal/Wattage(W)	6		
Temperatura de color/CCT(K)	3000K	4000K	5000K
Flujo luminoso/Luminous Flux(lm)	520	540	540
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz		
Regulable/Dimmable	NO		
CRI	≥80		
Casquillo/Lamp Head	GU10		
Angulo/Beam Angle(deg)	110°		
Material	Aluminio+PC/Aluminum+PC		
Dimensiones/Dimensions(mm)	Φ50*56		



LED GU10 Bulb


- Caracteristicas**
- \* Voltaje:AC 220-240V 50/60Hz 50mA
  - \* 15,000 hrs. vida util
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 60W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion

- Features**
- \* Voltage: AC 220-240V 50/60Hz 50mA
  - \* 15,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 60W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



6W GU10 515 Lumen

Item No.	R09158	R09159
Potencia nominal/Wattage(W)	6	
Temperatura de color/CCT(K)	3000K	5000K
Flujo luminoso/Luminous Flux(lm)	484	515
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz	
Regulable/Dimmable	NO	
CRI	≥80	
Casquillo/Lamp Head	GU10	
Angulo/Beam Angle(deg)	60°	
Material	Aluminio&PC / Aluminum&PC	
Dimensiones/Dimensions(mm)	Φ50*58	



LED GU10 Bulb


- Caracteristicas**
- \* Voltaje:AC 220-240V 50/60Hz 30mA
  - \* 15,000 hrs. vida util
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 35W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion

- Features**
- \* Voltage: AC 220-240V 50/60Hz 30mA
  - \* 15,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 35W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



4W GU10 320 Lumen

Item No.	R09194	R09195
Potencia nominal/Wattage(W)	4	
Temperatura de color/CCT(K)	3000K	5000K
Flujo luminoso/Luminous Flux(lm)	300	320
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz	
Regulable/Dimmable	NO	
CRI	≥80	
Casquillo/Lamp Head	GU10	
Angulo/Beam Angle(deg)	110°	
Material	Aluminio+Cristal/Aluminum+Glass	
Dimensiones/Dimensions(mm)	Φ50*53	







LED GU10 Bulb New

- Características**
- \* Voltaje:AC 220-240V 50/60Hz 34mA
  - \* 15,000 hrs. vida útil
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 60W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion


- Features**
- \* Voltage: AC 220-240V 50/60Hz 34mA
  - \* 15,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 60W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



7W GU10 570 Lumen




Item No.	R09254	R09255	R09256
Potencia nominal/Wattage(W)	7		
Temperatura de color/CCT(K)	2700K	3000K	4000K
Flujo luminoso/Luminous Flux(lm)	510	540	570
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz		
Regulable/Dimmable	NO		
CRI	≥80		
Casquillo/Lamp Head	GU10		
Angulo/Beam Angle(deg)	50°		
Material	Aluminio+PC/Aluminum+PC		
Dimensiones/Dimensions(mm)	Φ50*56		




LED GU10 Bulb New

- Características**
- \* Voltaje:AC 220-240V 50/60Hz 30mA
  - \* 15,000 hrs. vida útil
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 60W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion


- Features**
- \* Voltage: AC 220-240V 50/60Hz 30mA
  - \* 15,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 60W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



7W GU10 570 Lumen  
DIMMABLE



Item No.	R09257	R09258	R09259
Potencia nominal/Wattage(W)	7		
Temperatura de color/CCT(K)	2700K	3000K	4000K
Flujo luminoso/Luminous Flux(lm)	510	540	570
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz		
Regulable/Dimmable	YES		
CRI	≥80		
Casquillo/Lamp Head	GU10		
Angulo/Beam Angle(deg)	50°		
Material	Aluminio+Cristal/Aluminum+Glass		
Dimensiones/Dimensions(mm)	Φ50*56		



LED E14 Bulb

- Características**
- \* Voltaje:AC 220-240V 50/60Hz 35mA
  - \* 15,000 hrs. vida útil
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 40W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion


- Features**
- \* Voltage: AC 220-240V 50/60Hz 35mA
  - \* 15,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 40W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



4W E14 470 Lumen



Item No.	R09115
Potencia nominal/Wattage(W)	4
Temperatura de color/CCT(K)	2700K
Flujo luminoso/Luminous Flux(lm)	470
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz
Regulable/Dimmable	NO
CRI	≥80
Casquillo/Lamp Head	E14
Angulo/Beam Angle(deg)	360°
Material	Aluminio+Cristal/Aluminum+Glass
Dimensiones/Dimensions(mm)	Φ35*95



LED E14 Bulb

- Características**
- \* Voltaje:AC 220-240V 50/60Hz 35mA
  - \* 15,000 hrs. vida útil
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 40W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion


- Features**
- \* Voltage: AC 220-240V 50/60Hz 35mA
  - \* 15,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 40W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



4W E14 340 Lumen



Item No.	R09208
Potencia nominal/Wattage(W)	4
Temperatura de color/CCT(K)	2200K
Flujo luminoso/Luminous Flux(lm)	340
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz
Regulable/Dimmable	NO
CRI	≥80
Casquillo/Lamp Head	E14
Angulo/Beam Angle(deg)	360°
Material	Aluminio+Cristal/Aluminum+Glass
Dimensiones/Dimensions(mm)	Φ35*95





LED E14 Bulb

- Caracteristicas**
- \* Voltaje:AC 220-240V 50/60Hz 35mA
  - \* 15,000 hrs. vida util
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 40W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion


- Features**
- \* Voltage: AC 220-240V 50/60Hz 35mA
  - \* 15,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 40W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



4W E14 470 Lumen




Item No.	R09114
Potencia nominal/Wattage(W)	4
Temperatura de color/CCT(K)	2700K
Flujo luminoso/Luminous Flux(lm)	470
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz
Regulable/Dimmable	NO
CRI	≥80
Casquillo/Lamp Head	E14
Angulo/Beam Angle(deg)	360°
Material	Aluminio+Cristal/Aluminum+Glass
Dimensiones/Dimensions(mm)	Φ45*78



LED E14 Bulb

- Caracteristicas**
- \* Voltaje:AC 220-240V 50/60Hz 35mA
  - \* 15,000 hrs. vida util
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 40W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion


- Features**
- \* Voltage: AC 220-240V 50/60Hz 35mA
  - \* 15,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 40W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



4W E14 470 Lumen



Item No.	R09116
Potencia nominal/Wattage(W)	4
Temperatura de color/CCT(K)	2700K
Flujo luminoso/Luminous Flux(lm)	470
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz
Regulable/Dimmable	NO
CRI	≥80
Casquillo/Lamp Head	E14
Angulo/Beam Angle(deg)	360°
Material	Aluminio+Cristal/Aluminum+Glass
Dimensiones/Dimensions(mm)	Φ35*130



LED E14 Bulb


- Caracteristicas**
- \* Voltaje:AC 220-240V 50/60Hz 45mA
  - \* 15,000 hrs. vida util
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 40W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion

- Features**
- \* Voltage: AC 220-240V 50/60Hz 45mA
  - \* 15,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 40W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



5.5W E14 490 Lumen

Item No.	R09117	R09221	R09118
Potencia nominal/Wattage(W)		5.5	
Temperatura de color/CCT(K)	3000K	4000K	5000K
Flujo luminoso/Luminous Flux(lm)	470	480	490
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz		
Regulable/Dimmable	NO		
CRI	≥80		
Casquillo/Lamp Head	E14		
Angulo/Beam Angle(deg)	140°		
Material	Aluminio+PC+Cristal/Aluminum+PC+Glass		
Dimensiones/Dimensions(mm)	Φ45*82		



LED E14 Bulb


- Caracteristicas**
- \* Voltaje:AC 220-240V 50/60Hz 35mA
  - \* 15,000 hrs. vida util
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 40W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion

- Features**
- \* Voltage: AC 220-240V 50/60Hz 35mA
  - \* 15,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 40W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



4W E14 470 Lumen

Item No.	R09241	R09242
Potencia nominal/Wattage(W)		4
Temperatura de color/CCT(K)	3000K	4000K
Flujo luminoso/Luminous Flux(lm)	470	485
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz	
Regulable/Dimmable	NO	
CRI	≥80	
Casquillo/Lamp Head	E14	
Angulo/Beam Angle(deg)	360°	
Material	Aluminio+PC+Cristal/Aluminum+PC+Glass	
Dimensiones/Dimensions(mm)	Φ35*95	





LED E14 Bulb


- Caracteristicas**
- \* Voltaje:AC 220-240V/50Hz 55mA
  - \* 15,000 hrs. vida util
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 60W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion

- Features**
- \* Voltage: AC 220-240V/50Hz 55mA
  - \* 15,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 60W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



6.5W E14 800 Lumen

Item No.	R09239	R09240
Potencia nominal/Wattage(W)	6.5	
Temperatura de color/CCT(K)	3000K	4000K
Flujo luminoso/Luminous Flux(lm)	790	800
Tension nominal/Voltage(V)	AC 220-240V/50Hz	
Regulable/Dimmable	NO	
CRI	≥80	
Casquillo/Lamp Head	E14	
Angulo/Beam Angle(deg)	360°	
Material	Aluminio+Cristal/Aluminum+Glass	
Dimensiones/Dimensions(mm)	Φ45*78	



LED E27 Bulb


- Caracteristicas**
- \* Voltaje:AC 220-240V/50Hz 55mA
  - \* 15,000 hrs. vida util
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 60W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion

- Features**
- \* Voltage: AC 220-240V/50Hz 55mA
  - \* 15,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 60W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



6.5W E27 800 Lumen

Item No.	R09237	R09238
Potencia nominal/Wattage(W)	6.5	
Temperatura de color/CCT(K)	3000K	4000K
Flujo luminoso/Luminous Flux(lm)	790	800
Tension nominal/Voltage(V)	AC 220-240V/50Hz	
Regulable/Dimmable	NO	
CRI	≥80	
Casquillo/Lamp Head	E27	
Angulo/Beam Angle(deg)	360°	
Material	Aluminio+Cristal/Aluminum+Glass	
Dimensiones/Dimensions(mm)	Φ45*73	



LED E27 Bulb


- Caracteristicas**
- \* Voltaje:AC 220-240V 50/60Hz 55mA
  - \* 15,000 hrs. vida util
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 75W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion

- Features**
- \* Voltage: AC 220-240V 50/60Hz 55mA
  - \* 15,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 75W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



10W E27 1050 Lumen

Item No.	R09133	R09215	R09134
Potencia nominal/Wattage(W)	10		
Temperatura de color/CCT(K)	3000K	4000K	5000K
Flujo luminoso/Luminous Flux(lm)	1055	1080	1100
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz		
Regulable/Dimmable	NO		
CRI	≥80		
Casquillo/Lamp Head	E27		
Angulo/Beam Angle(deg)	320°		
Material	Aluminio+PC/Aluminum+PC		
Dimensiones/Dimensions(mm)	Φ60*112		



LED E27 Bulb New


- Caracteristicas**
- \* Voltaje:AC 220-240V 50/60Hz 65mA
  - \* 15,000 hrs. vida util
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 100W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion

- Features**
- \* Voltage: AC 220-240V 50/60Hz 65mA
  - \* 15,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 100W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



12W E27 1520 Lumen DIMMABLE

Item No.	R09251	R09252	R09253
Potencia nominal/Wattage(W)	12		
Temperatura de color/CCT(K)	2700K	3000K	4000K
Flujo luminoso/Luminous Flux(lm)	1440	1480	1520
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz		
Regulable/Dimmable	YES		
CRI	≥80		
Casquillo/Lamp Head	E27		
Angulo/Beam Angle(deg)	360°		
Material	Aluminio+Cristal/Aluminum+Glass		
Dimensiones/Dimensions(mm)	Φ60*108		





LED E27 Bulb

Caracteristicas

- \* Voltaje:AC 220-240V 50/60Hz 56mA
- \* 15,000 hrs. vida util
- \* Encendido instantaneo con potencia total
- \* Perfecta para reemplazar la lampara incandescente de 60W
- \* Baja temperatura al tacto
- \* Libre de mercurio, Libre de emision UV & IR
- \* Esta lampara no es idonea para la iluminacion de acentuacion

Features

- \* Voltage: AC 220-240V 50/60Hz 56mA
- \* 15,000hrs long life time
- \* Instant start with full bright output flick free
- \* Perfect replacement for 60W incandescent Bulb
- \* Low temperature,safety to touch
- \* No UV or IR emission, mercury FREE
- \* This lamp is not suitable for accent lighting





7W E27 800 Lumen

Item No.	R09131	R09250	R09211
Potencia nominal/Wattage(W)	7		
Temperatura de color/CCT(K)	2700K	3000K	4000K
Flujo luminoso/Luminous Flux(lm)	800		
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz		
Regulable/Dimmable	NO		
CRI	≥80		
Casquillo/Lamp Head	E27		
Angulo/Beam Angle(deg)	360°		
Material	Cristal / Glass		
Dimensiones/Dimensions(mm)	Φ60*108		



7W LED ↔ 60W Incandescent lamp (Lux.)



LED E27 Bulb

Caracteristicas

- \* Voltaje:AC 220-240V 50/60Hz 35mA
- \* 15,000 hrs. vida util
- \* Encendido instantaneo con potencia total
- \* Perfecta para reemplazar la lampara incandescente de 40W
- \* Baja temperatura al tacto
- \* Libre de mercurio, Libre de emision UV & IR
- \* Esta lampara no es idonea para la iluminacion de acentuacion

Features

- \* Voltage: AC 220-240V 50/60Hz 35mA
- \* 15,000hrs long life time
- \* Instant start with full bright output flick free
- \* Perfect replacement for 40W incandescent Bulb
- \* Low temperature,safety to touch
- \* No UV or IR emission, mercury FREE
- \* This lamp is not suitable for accent lighting





4W E27 470 Lumen

Item No.	R09132
Potencia nominal/Wattage(W)	4
Temperatura de color/CCT(K)	2700K
Flujo luminoso/Luminous Flux(lm)	470
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz
Regulable/Dimmable	NO
CRI	≥80
Casquillo/Lamp Head	E27
Angulo/Beam Angle(deg)	360°
Material	Cristal / Glass
Dimensiones/Dimensions(mm)	Φ45*73



4W LED ↔ 40W Incandescent lamp (Lux.)



LED E27 Bulb

Caracteristicas

- \* Voltaje:AC 220-240V 50/60Hz 75mA
- \* 15,000 hrs. vida util
- \* Encendido instantaneo con potencia total
- \* Perfecta para reemplazar la lampara incandescente de 75W
- \* Baja temperatura al tacto
- \* Libre de mercurio, Libre de emision UV & IR
- \* Esta lampara no es idonea para la iluminacion de acentuacion

Features

- \* Voltage: AC 220-240V 50/60Hz 75mA
- \* 15,000hrs long life time
- \* Instant start with full bright output flick free
- \* Perfect replacement for 55W incandescent Bulb
- \* Low temperature,safety to touch
- \* No UV or IR emission, mercury FREE
- \* This lamp is not suitable for accent lighting





9W E27 1055 Lumen

Item No.	R09234	R09235
Potencia nominal/Wattage(W)	9	
Temperatura de color/CCT(K)	3000K	4000K
Flujo luminoso/Luminous Flux(lm)	1055	1090
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz	
Regulable/Dimmable	NO	
CRI	≥80	
Casquillo/Lamp Head	E27	
Angulo/Beam Angle(deg)	360°	
Material	Cristal+PC+Metal/Glass+PC+Metal	
Dimensiones/Dimensions(mm)	Φ60*108	



9W LED ↔ 75W Incandescent lamp (Lux.)



LED E27 Bulb

Caracteristicas

- \* Voltaje:AC 220-240V 50/60Hz 45mA
- \* 15,000 hrs. vida util
- \* Encendido instantaneo con potencia total
- \* Perfecta para reemplazar la lampara incandescente de 40W
- \* Baja temperatura al tacto
- \* Libre de mercurio, Libre de emision UV & IR
- \* Esta lampara no es idonea para la iluminacion de acentuacion

Features

- \* Voltage: AC 220-240V 50/60Hz 45mA
- \* 15,000hrs long life time
- \* Instant start with full bright output flick free
- \* Perfect replacement for 40W incandescent Bulb
- \* Low temperature,safety to touch
- \* No UV or IR emission, mercury FREE
- \* This lamp is not suitable for accent lighting





5.5W E27 490 Lumen

Item No.	R09135	R09223	R09136
Potencia nominal/Wattage(W)	5.5		
Temperatura de color/CCT(K)	3000K	4000K	5000K
Flujo luminoso/Luminous Flux(lm)	470	480	490
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz		
Regulable/Dimmable	NO		
CRI	≥80		
Casquillo/Lamp Head	E27		
Angulo/Beam Angle(deg)	140°		
Material	Cristal+PC+Metal/Glass+PC+Metal		
Dimensiones/Dimensions(mm)	Φ45*78		



5.5W LED ↔ 40W Incandescent lamp (Lux.)





LED E27 Bulb

- Caracteristicas
- \* Voltaje:AC 220-240V 50/60Hz 60mA
  - \* 20,000 hrs. vida util
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 100W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion


- Features
- \* Voltage: AC 220-240V 50/60Hz 60mA
  - \* 20,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 100W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



11W E27 850 Lumen  
Dimmable



Item No.	R09137
Potencia nominal/Wattage(W)	11
Temperatura de color/CCT(K)	3000K
Flujo luminoso/Luminous Flux(lm)	850
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz
Regulable/Dimmable	YES
CRI	≥80
Casquillo/Lamp Head	E27
Angulo/Beam Angle(deg)	240°
Material	PBT+crystal/glass
Dimensiones/Dimensions(mm)	Φ60*110




LED E27 Bulb

- Caracteristicas
- \* Voltaje:AC 220-240V 50/60Hz 72mA
  - \* 15,000 hrs. vida util
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 125W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion


- Features
- \* Voltage: AC 220-240V 50/60Hz 72mA
  - \* 15,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 125W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



14W E27 1510 Lumen



Item No.	R09139	R09140
Potencia nominal/Wattage(W)	14	
Temperatura de color/CCT(K)	3000K	4000K
Flujo luminoso/Luminous Flux(lm)	1460	1510
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz	
Regulable/Dimmable	NO	
CRI	≥80	
Casquillo/Lamp Head	E27	
Angulo/Beam Angle(deg)	240°	
Material	PBT+crystal/glass	
Dimensiones/Dimensions(mm)	Φ60*120	



LED E27 Bulb

- Caracteristicas
- \* Voltaje:AC 220-240V 50/60Hz 60mA
  - \* 25,000 hrs. vida util
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 140W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion


- Features
- \* Voltage: AC 220-240V 50/60Hz 60mA
  - \* 25,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 140W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



14W E27 1309 Lumen  
G95



Item No.	R09122	R09123
Potencia nominal/Wattage(W)	14	
Temperatura de color/CCT(K)	3000K	5000K
Flujo luminoso/Luminous Flux(lm)	1259	1309
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz	
Regulable/Dimmable	NO	
CRI	≥80	
Casquillo/Lamp Head	E27	
Angulo/Beam Angle(deg)	180°	
Material	Aluminio+PC/Aluminum+PC	
Dimensiones/Dimensions(mm)	Φ95*131	




LED E27 Bulb

- Caracteristicas
- \* Voltaje:AC 220-240V 50/60Hz 165mA
  - \* 15,000 hrs. vida util
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 175W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion


- Features
- \* Voltage: AC 220-240V 50/60Hz 165mA
  - \* 15,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 175W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



20W E27 2000 Lumen  
G120



Item No.	R09212	R09213
Potencia nominal/Wattage(W)	20	
Temperatura de color/CCT(K)	3000K	4000K
Flujo luminoso/Luminous Flux(lm)	1900	2000
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz	
Regulable/Dimmable	NO	
CRI	≥80	
Casquillo/Lamp Head	E27	
Angulo/Beam Angle(deg)	270°	
Material	Aluminio+Crystal/Aluminum+Glass	
Dimensiones/Dimensions(mm)	Φ120*157	





## LED E27 Bulb

### Caracteristicas


- \* Voltaje:AC 220-240V 50/60Hz 56mA
- \* 15,000 hrs. vida util
- \* Encendido instantaneo con potencia total
- \* Perfecta para reemplazar la lampara incandescente de 60W
- \* Baja temperatura al tacto
- \* Libre de mercurio, Libre de emision UV & IR
- \* Esta lampara no es idonea para la iluminacion de acentuacion

### Features

- \* Voltage: AC 220-240V 50/60Hz 56mA
- \* 15,000hrs long life time
- \* Instant start with full bright output flick free
- \* Perfect replacement for 60W incandescent Bulb
- \* Low temperature,safety to touch
- \* No UV or IR emission, mercury FREE
- \* This lamp is not suitable for accent lighting



6.5W E27 720 Lumen  
G95



Item No.	R09244	R09245
Potencia nominal/Wattage(W)	6.5	
Temperatura de color/CCT(K)	3000K	4000K
Flujo luminoso/Luminous Flux(lm)	720	740
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz	
Regulable/Dimmable	NO	
CRI	≥80	
Casquillo/Lamp Head	E27	
Angulo/Beam Angle(deg)	360°	
Material	Aluminio+Glass Lens/Aluminum+Glass Lens	
Dimensiones/Dimensions(mm)	Φ95*133	

## LED E27 Bulb

### Caracteristicas


- \* Voltaje:AC 220-240V 50/60Hz 56mA
- \* 15,000 hrs. vida util
- \* Encendido instantaneo con potencia total
- \* Perfecta para reemplazar la lampara incandescente de 60W
- \* Baja temperatura al tacto
- \* Libre de mercurio, Libre de emision UV & IR
- \* Esta lampara no es idonea para la iluminacion de acentuacion

### Features

- \* Voltage: AC 220-240V 50/60Hz 56mA
- \* 15,000hrs long life time
- \* Instant start with full bright output flick free
- \* Perfect replacement for 60W incandescent Bulb
- \* Low temperature,safety to touch
- \* No UV or IR emission, mercury FREE
- \* This lamp is not suitable for accent lighting



6.5W E27 650 Lumen  
G95



Item No.	R09229
Potencia nominal/Wattage(W)	6.5
Temperatura de color/CCT(K)	2200K
Flujo luminoso/Luminous Flux(lm)	650
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz
Regulable/Dimmable	NO
CRI	≥80
Casquillo/Lamp Head	E27
Angulo/Beam Angle(deg)	360°
Material	Aluminio+Cristal/Aluminum+Glass
Dimensiones/Dimensions(mm)	Φ95*133

## LED E27 Bulb

### Caracteristicas


- \* Voltaje:AC 220-240V 50/60Hz 45mA
- \* 15,000 hrs. vida util
- \* Encendido instantaneo con potencia total
- \* Perfecta para reemplazar la lampara incandescente de 60W
- \* Baja temperatura al tacto
- \* Libre de mercurio, Libre de emision UV & IR
- \* Esta lampara no es idonea para la iluminacion de acentuacion

### Features

- \* Voltage: AC 220-240V 50/60Hz 45mA
- \* 15,000hrs long life time
- \* Instant start with full bright output flick free
- \* Perfect replacement for 60W incandescent Bulb
- \* Low temperature,safety to touch
- \* No UV or IR emission, mercury FREE
- \* This lamp is not suitable for accent lighting



8W E27 720 Lumen  
G95  
Dimmable



Item No.	R09246
Potencia nominal/Wattage(W)	8
Temperatura de color/CCT(K)	3000K
Flujo luminoso/Luminous Flux(lm)	720
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz
Regulable/Dimmable	YES
CRI	≥80
Casquillo/Lamp Head	E27
Angulo/Beam Angle(deg)	360°
Material	Aluminio+Cristal/Aluminum+Glass
Dimensiones/Dimensions(mm)	Φ95*133

## LED E27 Bulb

### Caracteristicas


- \* Voltaje:AC 220-240V 50/60Hz 56mA
- \* 15,000 hrs. vida util
- \* Encendido instantaneo con potencia total
- \* Perfecta para reemplazar la lampara incandescente de 60W
- \* Baja temperatura al tacto
- \* Libre de mercurio, Libre de emision UV & IR
- \* Esta lampara no es idonea para la iluminacion de acentuacion

### Features

- \* Voltage: AC 220-240V 50/60Hz 56mA
- \* 15,000hrs long life time
- \* Instant start with full bright output flick free
- \* Perfect replacement for 60W incandescent Bulb
- \* Low temperature,safety to touch
- \* No UV or IR emission, mercury FREE
- \* This lamp is not suitable for accent lighting



6.5W E27 650 Lumen  
G125



Item No.	R09230
Potencia nominal/Wattage(W)	6.5
Temperatura de color/CCT(K)	2200K
Flujo luminoso/Luminous Flux(lm)	650
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz
Regulable/Dimmable	NO
CRI	≥80
Casquillo/Lamp Head	E27
Angulo/Beam Angle(deg)	360°
Material	Aluminio+Cristal/Aluminum+Glass
Dimensiones/Dimensions(mm)	Φ125*176



LED E27 ST64 Bulb



- Caracteristicas**
- \* Voltaje:AC 220-240V 50/60Hz 45mA
  - \* 15,000 hrs. vida util
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 60W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion

- Features**
- \* Voltage: AC 220-240V 50/60Hz 45mA
  - \* 15,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 60W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



8W E27 800 Lumen  
ST64  
Dimmable

Item No.	R09206
Potencia nominal/Wattage(W)	8
Temperatura de color/CCT(K)	2200K
Flujo luminoso/Luminous Flux(lm)	800
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz
Regulable/Dimmable	YES
CRI	≥80
Casquillo/Lamp Head	E27
Angulo/Beam Angle(deg)	360°
Material	Aluminio+Cristal/Aluminum+Glass
Dimensiones/Dimensions(mm)	Φ64*142



LED E27 G95 Bulb



- Caracteristicas**
- \* Voltaje:AC 220-240V 50/60Hz 45mA
  - \* 15,000 hrs. vida util
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 60W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion

- Features**
- \* Voltage: AC 220-240V 50/60Hz 45mA
  - \* 15,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 60W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



8W E27 800 Lumen  
G95  
Dimmable

Item No.	R09204
Potencia nominal/Wattage(W)	8
Temperatura de color/CCT(K)	2200K
Flujo luminoso/Luminous Flux(lm)	800
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz
Regulable/Dimmable	YES
CRI	≥80
Casquillo/Lamp Head	E27
Angulo/Beam Angle(deg)	360°
Material	Aluminio+Cristal/Aluminum+Glass
Dimensiones/Dimensions(mm)	Φ95*135



LED E27 Bulb


- Caracteristicas**
- \* Voltaje:AC 220-240V 50/60Hz 56mA
  - \* 15,000 hrs. vida util
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 60W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion

- Features**
- \* Voltage: AC 220-240V 50/60Hz 56mA
  - \* 15,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 60W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



6.5W E27 650 Lumen  
ST64

Item No.	R09228
Potencia nominal/Wattage(W)	6.5
Temperatura de color/CCT(K)	2200K
Flujo luminoso/Luminous Flux(lm)	650
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz
Regulable/Dimmable	NO
CRI	≥80
Casquillo/Lamp Head	E27
Angulo/Beam Angle(deg)	360°
Material	Aluminio+Cristal/Aluminum+Glass
Dimensiones/Dimensions(mm)	Φ64*138



LED E27 G125 Bulb



- Caracteristicas**
- \* Voltaje:AC 220-240V 50/60Hz 45mA
  - \* 15,000 hrs. vida util
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 60W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion

- Features**
- \* Voltage: AC 220-240V 50/60Hz 45mA
  - \* 15,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 60W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



8W E27 800 Lumen  
G125  
Dimmable

Item No.	R09205
Potencia nominal/Wattage(W)	8
Temperatura de color/CCT(K)	2200K
Flujo luminoso/Luminous Flux(lm)	800
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz
Regulable/Dimmable	YES
CRI	≥80
Casquillo/Lamp Head	E27
Angulo/Beam Angle(deg)	360°
Material	Aluminio+Cristal/Aluminum+Glass
Dimensiones/Dimensions(mm)	Φ125*170





LED E27 T30 Bulb

- Caracteristicas**
- \* Voltaje:AC 220-240V 50/60Hz 430mA
  - \* 20,000 hrs. vida util
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 55W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion


- Features**
- \* Voltage: AC 220-240V 50/60Hz 430mA
  - \* 20,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 55W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



6W E27 575 Lumen  
T30




Item No.	R09233
Potencia nominal/Wattage(W)	6
Temperatura de color/CCT(K)	2400K
Flujo luminoso/Luminous Flux(lm)	575
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz
Regulable/Dimmable	NO
CRI	≥80
Casquillo/Lamp Head	E27
Angulo/Beam Angle(deg)	360°
Material	Aluminio+Cristal/Aluminum+Glass
Dimensiones/Dimensions(mm)	Φ30*185



LED GX53 Bulb

- Caracteristicas**
- \* Voltaje:AC 100-250V 50/60Hz 80mA
  - \* 20,000 hrs. vida util
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 80W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion


- Features**
- \* Voltage: AC 100-250V 50/60Hz 80mA
  - \* 20,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 80W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



9W GX53 730 Lumen



Item No.	R09224	R09225
Potencia nominal/Wattage(W)	9	
Temperatura de color/CCT(K)	3000K	4000K
Flujo luminoso/Luminous Flux(lm)	730	740
Tension nominal/Voltage(V)	AC 100-250V 50/60Hz	
Regulable/Dimmable	NO	
CRI	≥80	
Casquillo/Lamp Head	GX53	
Angulo/Beam Angle(deg)	120°	
Material	estampacion de aluminio&PC / Stamping aluminium&PC	
Dimensiones/Dimensions(mm)	Φ75*24	



LED E27 T30 Bulb

- Caracteristicas**
- \* Voltaje:AC 220-240V 50/60Hz 430mA
  - \* 20,000 hrs. vida util
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 70W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion


- Features**
- \* Voltage: AC 220-240V 50/60Hz 430mA
  - \* 20,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 70W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



7W E27 660 Lumen  
T30




Item No.	R09232
Potencia nominal/Wattage(W)	7
Temperatura de color/CCT(K)	2400K
Flujo luminoso/Luminous Flux(lm)	660
Tension nominal/Voltage(V)	AC 220-240V 50/60Hz
Regulable/Dimmable	NO
CRI	≥80
Casquillo/Lamp Head	E27
Angulo/Beam Angle(deg)	360°
Material	Aluminio+Cristal/Aluminum+Glass
Dimensiones/Dimensions(mm)	Φ30*300



LED GX53 Bulb

- Caracteristicas**
- \* Voltaje:AC 100-250V 50/60Hz 104mA
  - \* 20,000 hrs. vida util
  - \* Encendido instantaneo con potencia total
  - \* Perfecta para reemplazar la lampara incandescente de 100W
  - \* Baja temperatura al tacto
  - \* Libre de mercurio, Libre de emision UV & IR
  - \* Esta lampara no es idonea para la iluminacion de acentuacion


- Features**
- \* Voltage: AC 100-250V 50/60Hz 104mA
  - \* 20,000hrs long life time
  - \* Instant start with full bright output flick free
  - \* Perfect replacement for 100W incandescent Bulb
  - \* Low temperature,safety to touch
  - \* No UV or IR emission, mercury FREE
  - \* This lamp is not suitable for accent lighting



12W GX53 930 Lumen



Item No.	R09248	R09249
Potencia nominal/Wattage(W)	12	
Temperatura de color/CCT(K)	3000K	4000K
Flujo luminoso/Luminous Flux(lm)	930	960
Tension nominal/Voltage(V)	AC 100-250V 50/60Hz	
Regulable/Dimmable	NO	
CRI	≥80	
Casquillo/Lamp Head	GX53	
Angulo/Beam Angle(deg)	120°	
Material	estampacion de aluminio&PC / Stamping aluminium&PC	
Dimensiones/Dimensions(mm)	Φ74*28	





REFERENCIA	FAMILIA	PAGE
1326	FLAME	404
1388	AVORIAZ	428
1391	AVORIAZ	428
1394	AVORIAZ	428
1397	AVORIAZ	384
1398	AVORIAZ	384
1399	AVORIAZ	384
1400	FLAME	432
5120	TOJA	98
5121	TOJA	98
5410	ZERO E27	120
5411	ZERO E27	120
5622	ARUBA	160
5623	ARUBA	160
5624	ARUBA	160
5625	ARUBA	160
5626	ARUBA	192
5627	ARUBA	192
5628	ARUBA	192
5629	ARUBA	192
5632	KAILUA	196
5633	KAILUA	196
5714	CABARETE	77
5715	CABARETE	76
5717	BORACAY	198
5718	BORACAY	198
6015	ARUBA	190
6016	ARUBA	190
6043	PETACA	108
6044	ARUBA	208
6045	ARUBA	208
6046	BOAVISTA	78
6047	BOAVISTA	78
6048	BOAVISTA	79
6049	BOAVISTA	79
6050	BOAVISTA	79
6051	BOAVISTA	79
6070	TARIFA	82
6071	TARIFA	82

6072	TARIFA	82
6075	PREA	84
6076	PREA	84
6077	PREA	84
6080	CAYMAN	74
6081	CAYMAN	74
6082	CAYMAN	74
6083	CAYMAN	74
6091	CAICOS	86
6092	CAICOS	86
6093	CAICOS	86
6211	KINKÉ	378
6212	KINKÉ	376
6213	KINKÉ	380
6214	KINKÉ	380
6215	KINKÉ	380
6218	KINKÉ	380
6220	ASIMETRIC	56
6221	ASIMETRIC	56
6222	ASIMETRIC	56
6230	MURAL	94
6253	TOJA	98
6254	TOJA	98
6280	SAL	186
6281	SAL	186
6282	SAL	186
6283	SAL	72/186
6284	SAL	72
6370	JERI	102
6374	JERI	102
6380	PARACURU	100
6381	PARACURU	100
6382	PARACURU	100
6383	PARACURU	100
6384	PARACURU	100
6385	PARACURU	100
6390	GRACIOSA	243
6392	GRACIOSA	242
6395	MEDANO	236
6396	MEDANO	236

6397	GRACIOSA	242
6398	MEDANO	236
6399	MEDANO	236
6400	GARDA	226
6401	GARDA	226
6402	GARDA	226
6403	GARDA	226
6405	ATLANTIS	258
6406	ATLANTIS	258
6470	RODAS	356
6480	K2	396
6481	K2	396
6482	VOLCANO	314
6483	VOLCANO	314
6484	K2	396
6490	MERIBEL	408
6491	ASTUN	402
6492	MERIBEL	310
6493	MERIBEL	310
6494	MERIBEL	308
6495	MERIBEL	308
6496	CERLER	357
6497	TIGNES	357
6498	TIGNES	422
6499	TIGNES	422
6508	TEJA	312
6510	KANDANCHU	322
6511	KANDANCHU	322
6512	KANDANCHU	323
6513	KANDANCHU	323
6514	KANDANCHU	322
6515	KANDANCHU	322
6516	KANDANCHU	323
6517	KANDANCHU	323
6520	DAVOS	324
6521	DAVOS	324
6522	DAVOS	324
6523	DAVOS	324
6524	DAVOS	324
6525	TRIAX	332

6526	TRIAX	332
6527	DAVOS	324
6530	SOCHI	334
6531	SOCHI	334
6534	BORA	336
6535	BORA	336
6536	BORA	336
6537	BORA	336
6538	BORA	336
6539	BORA	336
6540	ARCS	298
6541	ARCS	298
6542	JACKSON	354
6543	JACKSON	354
6545	ESPIGA	430
6546	ESPIGA	430
6547	ESPIGA	430
6550	MAYA	410
6551	MAYA	304
6552	MAYA	304
6553	MAYA	362
6554	MAYA	362
6555	MAYA	382
6558	IGUAZU	316
6559	IGUAZU	316
6560	MURAL	118
6561	MURAL	118
6562	MURAL	171
6563	MURAL	181
6620	SAONA SUP	122
6621	SAONA SUP	122
6622	SAONA SUP	122
6623	SAONA SUP	122
6624	SAONA SUP	122
6625	SAONA SUP	122
6626	SAONA SUP	122
6627	SAONA SUP	122
6628	SAONA SUP	124
6629	SAONA SUP	124
6630	SAONA SUP	124

6631	SAONA SUP	124
6632	SAONA SUP	124
6633	SAONA SUP	124
6634	SAONA SUP	124
6635	SAONA SUP	124
6700	TORCH	66
6701	TORCH	66
6702	TORCH	68
6703	TORCH	68
6710	SAL	186
6711	SAL	186
6712	SAL	186
6713	SAL	72/186
6714	SAL	72
6715	ZANZIBAR	172
6716	ZANZIBAR	172
6717	SAL	210
6718	SAL	210
6735	TORCH	178
6736	TORCH	178
6737	TORCH	168
6738	TORCH	168
6750	ZANZIBAR	58
6751	ZANZIBAR	62
6752	ZANZIBAR	58
6753	ZANZIBAR	62
6754	ZANZIBAR	60
6755	ZANZIBAR	60
6760	MORNE	54
6761	MORNE	54
6762	MORNE	54
6763	MORNE	54
6768	IGUAZU	318
6769	IGUAZU	318
6770	RUKA	306
6771	RUKA	412
6772	RUKA	412
6773	RUKA	412
6774	RUKA	306
6810	COMFORT IP	259

6811	COMFORT IP	259
6812	COMFORT IP	259
6813	COMFORT IP	259
6820	GOKOVA	80
6821	GOKOVA	80
6825	TORCH	158
6826	TORCH	158
6827	TORCH	116
6828	TORCH	116
6830	GOWER	188
6831	GOWER	188
6832	GOWER	188
6833	GOWER	188
6835	LAMBORJINI	253
6837	LAMBORJINI	253
6838	LAMBORJINI	253
6839	LAMBORJINI	252
6840	LAMBORJINI	252
6841	LAMBORJINI	252
6842	LAMBORJINI	252
6843	LAMBORJINI	252
6844	LAMBORJINI	252
6845	LAMBORJINI	252
6846	LAMBORJINI	252
6850	CYCLE	300
6851	CYCLE	300
6855	GUINCHO	222
6856	GUINCHO	222
6857	GUINCHO	222
6858	GUINCHO	222
6859	GUINCHO	222
6860	GUINCHO	222
6861	GUINCHO	222
6862	GUINCHO	222
6865	FUERTEVENTURA	64
6866	FUERTEVENTURA	64
6870	TENERIFE	104
6871	TENERIFE	104
6875	LANZAROTE	106
6876	LANZAROTE	106



6900	BRANDON	250
6901	BRANDON	250
6902	BRANDON	250
6903	BRANDON	250
6905	ASTUN	402
6906	ASTUN	402
6907	ASTUN	402
7011	BAKER	434
7012	BAKER	434
7013	BAKER	436
7014	BAKER	436
7015	BAKER	434
7016	BAKER	434
7017	BAKER	436
7018	BAKER	436
7021	ASPEN	438
7022	ASPEN	438
7023	ASPEN	438
7024	ASPEN	438
7025	ASPEN	438
7026	ASPEN	438
7027	ASPEN	440
7028	ASPEN	440
7029	ASPEN	440
7030	ASPEN	440
7031	ASPEN	440
7032	ASPEN	440
7037	KANDANCHU	322
7038	KANDANCHU	322
7039	KANDANCHU	323
7040	KANDANCHU	323
7045	ALPINE	346
7046	ALPINE	346
7050	UTAH	338
7051	UTAH	338
7052	UTAH	338
7055	BACHELOR	368
7056	BACHELOR	368
7060	CHAMONIX	366
7061	CHAMONIX	366

7062	CHAMONIX	348
7063	CHAMONIX	348
7065	VERBIER	364
7066	VERBIER	364
7070	SOLDEN	345
7071	SOLDEN	345
7072	SOLDEN	344
7073	SOLDEN	344
7080	GUINCHO	222
7081	GUINCHO	222
7082	GUINCHO	222
7083	GUINCHO	222
7085	MERIBEL	406
7086	MERIBEL	340
7088	CHEVALIER	414
7090	SAPPPORO	400
7091	SAPPPORO	400
7092	SAPPPORO	400
7093	SAPPPORO	400
7098	YETI	342
7100	K2	398
7101	K2	398
7105	TAOS	420
7106	TAOS	420
7107	TAOS	426
7108	TAOS	350
7109	TAOS	350
7110	COOK	110
7111	COOK	110
7115	K3	394
7116	K3	394
7130	POLINESIA	374
7131	POLINESIA	372
7133	POLINESIA	302
7175	DURBAN	50
7176	DURBAN	50
7177	DURBAN	50
7180	LEVI	353
7181	LEVI	353
7182	LEVI	352

7183	LEVI	352
7184	LEVI	370
7185	LEVI	370
7186	LEVI	371
7187	LEVI	371
7197	DURBAN	52
7198	DURBAN	52
7199	DURBAN	52
7200	FUJI	212
7201	FUJI	212
7202	FUJI	212
7203	FUJI	212
7204	FUJI	212
7205	FUJI	212
7206	FUJI	212
7207	FUJI	212
7208	FUJI	214
7209	FUJI	214
7210	FUJI	214
7211	FUJI	214
7212	FUJI	214
7213	FUJI	214
7214	FUJI	214
7215	FUJI	214
7216	FUJI	212
7217	FUJI	212
7218	FUJI	212
7219	FUJI	212
7220	FUJI	212
7221	FUJI	212
7222	FUJI	212
7223	FUJI	212
7224	FUJI	212
7240	POLAR	48
7241	POLAR	48
7292	VENUS	40
7293	VENUS	40
7294	IOS	184
7295	IOS	184
7296	ERIS	42

7297	ERIS	42
7298	ERIS	44
7299	ERIS	44
7300	ERIS	46
7301	ERIS	46
7305	ORION	144
7306	ORION	146
7307	ORION	148
7308	ORION	146
7310	SIRIO	154
7311	SIRIO	156
7312	SIRIO	150
7313	SIRIO	153
7315	IPSILON	200
7316	IPSILON	200
7317	IPSILON	202
7318	IPSILON	202
7319	IPSILON	200
7320	IPSILON	200
7321	IPSILON	200
7322	IPSILON	200
7360	TIRAS LED STRIPS	261
7361	TIRAS LED STRIPS	261
7362	TIRAS LED STRIPS	261
7363	TIRAS LED STRIPS	262
7364	TIRAS LED STRIPS	262
7365	TIRAS LED STRIPS	262
7366	TIRAS LED STRIPS	260
7367	TIRAS LED STRIPS	260
7368	TIRAS LED STRIPS	260
7369	TIRAS LED STRIPS	263
7370	TIRAS LED STRIPS	263
7371	DRIVER TIRAS LED STRIPS	276
7372	DRIVER TIRAS LED STRIPS	276
7373	DRIVER TIRAS LED STRIPS	276
7374	DRIVER TIRAS LED STRIPS	276
7375	DRIVER TIRAS LED STRIPS	276
7376	DRIVER TIRAS LED STRIPS	277

7377	DRIVER TIRAS LED STRIPS	277
7378	DRIVER TIRAS LED STRIPS	275
7379	DRIVER TIRAS LED STRIPS	275
7380	DRIVER TIRAS LED STRIPS	275
7381	PERFILES LED PROFILES	264
7382	PERFILES LED PROFILES	264
7383	PERFILES LED PROFILES	264
7384	PERFILES LED PROFILES	264
7385	PERFILES LED PROFILES	264
7386	PERFILES LED PROFILES	264
7387	PERFILES LED PROFILES	264
7388	PERFILES LED PROFILES	264
7389	PERFILES LED PROFILES	264
7390	PERFILES LED PROFILES	264
7391	PERFILES LED PROFILES	264
7392	PERFILES LED PROFILES	265
7393	PERFILES LED PROFILES	265
7394	PERFILES LED PROFILES	265
7395	PERFILES LED PROFILES	265
7396	PERFILES LED PROFILES	265
7397	PERFILES LED PROFILES	265
7398	PERFILES LED PROFILES	265
7399	PERFILES LED PROFILES	265
7400	PERFILES LED PROFILES	265
7401	PERFILES LED PROFILES	265
7402	PERFILES LED PROFILES	265
7403	TIRAS LED STRIPS	263
7404	TIRAS LED STRIPS	263
7405	TIRAS LED STRIPS	263
7406	TIRAS LED STRIPS	263
7407	PERFILES LED PROFILES	274
7408	PERFILES LED PROFILES	274
7409	PERFILES LED PROFILES	274
7410	PERFILES LED PROFILES	274

7411	PERFILES LED PROFILES	274
7412	PERFILES LED PROFILES	274
7413	PERFILES LED PROFILES	274
7414	PERFILES LED PROFILES	274
7415	PERFILES LED PROFILES	274
7416	PERFILES LED PROFILES	274
7417	PERFILES LED PROFILES	268
7418	PERFILES LED PROFILES	268
7419	PERFILES LED PROFILES	268
7420	URANO	285
7421	URANO	285
7422	URANO	285
7423	URANO	287
7424	URANO	287
7425	URANO	287
7426	URANO	289
7427	URANO	289
7428	URANO	289
7429	URANO	291
7430	URANO	291
7431	URANO	291
7435	DAVOS XL	328
7436	DAVOS XL	328
7437	DAVOS XL	328
7438	DAVOS XL	328
7451	NEPTUNO	228
7452	NEPTUNO	228
7453	NEPTUNO	228
7454	NEPTUNO	228
7460	MURAL	94
7462	MURAL	118
7463	MURAL	118
7464	MURAL	170
7465	MURAL	180
7470	KANDANCHU	320
7471	KANDANCHU	320
7472	KANDANCHU	320
7473	KANDANCHU	320



7475	ORION	140
7476	ORION	142
7480	MORNE	54
7481	MORNE	54
7482	MORNE	54
7483	MORNE	54
7484	MORNE	54
7510	EYES	166
7511	EYES	166
7512	EYES	176
7513	EYES	36
7514	EYES	36
7515	SAL	164
7516	SAL	164
7517	SAL	174
7518	SAL	70
7519	SAL	70
7520	SAL	164
7521	SAL	164
7522	SAL	174
7523	SAL	70
7524	SAL	70
7535	GUINCHO GU10	224
7536	GUINCHO GU10	224
7540	HANOK	130
7541	HANOK	130
7542	HANOK	128
7543	HANOK	128
7544	HANOK	130
7545	HANOK	130
7546	HANOK	128
7547	HANOK	128
7548	HANOK	132
7549	HANOK	132
7550	HANOK	132
7551	HANOK	132
7552	HANOK	132
7553	HANOK	132
7554	HANOK	134
7555	HANOK	134

7556	HANOK	134
7557	HANOK	134
7558	HANOK	134
7559	HANOK	134
7569	HANOK	128
7590	KUBICK	30
7591	KUBICK	30
7592	KUBICK	30
7593	KUBICK	30
7594	KUBICK	30
7595	KUBICK	30
7596	KUBICK	30
7597	KUBICK	30
7640	BAKER	434
7641	BAKER	436
7642	BAKER	434
7643	BAKER	436
7645	DAVOS	326
7646	DAVOS	326
7647	DAVOS	326
7648	DAVOS	326
7649	DAVOS	326
7650	DAVOS	326
7651	DAVOS XL	328
7652	DAVOS XL	328
7653	DAVOS XL	328
7654	DAVOS XL	328
7693	LUPPI	28
7694	LUPPI	28
7695	LUPPI	28
7720	GOA	34
7721	GOA	34
7730	GLACIAR	182
7731	GLACIAR	182
7732	GLACIAR	182
7733	GLACIAR	182
7734	GLACIAR	182
7735	GLACIAR	182
7740	BASICO GU10	246
7741	BASICO GU10	246

7742	BASICO GU10	246
7743	BASICO GU10	246
7760	KUBICK	30
7761	KUBICK	30
7762	KUBICK	30
7763	KUBICK	30
7770	HANOK	26
7771	HANOK	26
7772	HANOK	26
7773	HANOK	26
7774	HANOK	24
7775	HANOK	24
7776	HANOK	24
7777	HANOK	24
7778	HANOK	24
7780	PAGODA	206
7781	PAGODA	206
7782	PAGODA	206
7783	PAGODA	206
7784	PAGODA	136
7785	PAGODA	136
7786	PAGODA	136
7787	PAGODA	136
7788	PAGODA	204
7789	PAGODA	204
7790	PAGODA	138
7791	PAGODA	138
7813	ARCS	298
7814	ARCS	298
7815	DAVOS DOUBLE	330
7816	DAVOS DOUBLE	330
7817	DAVOS DOUBLE	330
7818	DAVOS DOUBLE	330
7819	DAVOS DOUBLE	330
7820	DAVOS DOUBLE	330
7821	DAVOS DOUBLE	330
7822	DAVOS DOUBLE	330
7823	CAYMAN	74
7824	CAYMAN	74
7825	CAYMAN	74

7826	CAYMAN	74
7827	NEPTUNO	228
7828	NEPTUNO	228
7829	GARDA	226
7830	GARDA	226
7831	GARDA	226
7832	GARDA	226
7833	GARDA	226
7834	GARDA	226
7840	MURAL	94
7841	MURAL	94
7853	CAYMAN	74
7854	CAYMAN	74
7855	RECESSED BASES EMPOTRAR	162
7856	RECESSED BASES EMPOTRAR	162
7857	RECESSED BASES EMPOTRAR	162
7858	RECESSED BASES EMPOTRAR	162
7859	RECESSED BASES EMPOTRAR	162
7900	KANDANCHU	358
7901	KANDANCHU	358
7902	KANDANCHU	358
7903	KANDANCHU	358
7904	KANDANCHU	359
7905	KANDANCHU	359
7906	KANDANCHU	359
7907	KANDANCHU	359
7908	VOLCANO	360
7910	TOBAGO	22
7911	TOBAGO	22
7912	TOBAGO	22
7913	TOBAGO	22
7914	TOBAGO	22
7915	TOBAGO	22
7928	BERET	297
7929	BERET	296
7930	RELAX	386
7931	RELAX	386
7932	RELAX	386
7933	RELAX	388
7934	RELAX	388

7935	RELAX	388
7936	IOS	126
7937	IOS	126
7945	HANOK	112
7946	HANOK	112
7947	HANOK	112
7948	HANOK	112
7949	HANOK	112
7950	HANOK	112
7951	HANOK	112
7952	HANOK	112
7953	HANOK	112
7961	SAL	114
7962	SAL	114
7985	K4	392
7986	K4	392
7987	K4	392
7988	K5	390
7989	K5	390
7990	LOTUS	294
7991	LOTUS	294
7992	LOTUS	294
7993	LOTUS	294
7994	LOTUS	294
7995	LOTUS	294
7996	LOTUS	294
7997	LOTUS	294
8010	VENUS	38
8011	VENUS	38
8012	VENUS	38
8013	VENUS	38
8034	VENUS	38
8035	VENUS	38
8060	PERFILES LED PROFILES	268
8061	PERFILES LED PROFILES	268
8062	PERFILES LED PROFILES	268
8063	PERFILES LED PROFILES	268
8064	PERFILES LED PROFILES	266
8065	PERFILES LED PROFILES	266
8066	PERFILES LED PROFILES	266

8067	PERFILES LED PROFILES	272
8068	PERFILES LED PROFILES	272
8069	PERFILES LED PROFILES	272
8070	PERFILES LED PROFILES	270
8071	PERFILES LED PROFILES	270
8072	PERFILES LED PROFILES	270
8087	TAHITIXL	18
8088	TAHITIXL	18
8089	TAHITIXL	18
8090	TAHITIXL	18
8091	ALTEA	20
8092	ALTEA	20
8093	ALTEA	20
8094	ALTEA	20
8095	ALTEA	20
8096	ALTEA	20
8097	ALTEA	20
8098	ALTEA	20
8108	CHICAGO	418
8109	CHICAGO	418
8122	ORION	16
8123	ORION	16
8124	ORION	16
8125	ORION	16
8126	ORION	16
8127	ORION	16
8128	ORION	16
8129	ORION	16
8130	ORION	16
8151	ALPINE	416
8152	ANDES	292
8153	ANDES	292
8154	ANDES	292
8155	QUEBEC	424
8156	FUJI	14
8157	FUJI	14
8158	FUJI	14
8159	FUJI	14
9953074	SISTEMAS TIRAS STRIPS	283
9955901	SISTEMAS TIRAS STRIPS	280



9955905	SISTEMAS TIRAS STRIPS	281
9955911	SISTEMAS TIRAS STRIPS	278
9955912	SISTEMAS TIRAS STRIPS	279
9955921	SISTEMAS TIRAS STRIPS	282
C0001	BASICO GU10	244
C0002	BASICO GU10	244
C0003	BASICO GU10	244
C0004	BASICO GU10	244
C0005	BASICO GU10	244
C0006	BASICO GU10	244
C0007	BASICO GU10	244
C0008	BASICO GU10	244
C0041	CABRERA	234
C0042	CABRERA	234
C0043	CABRERA	234
C0044	CABRERA	234
C0047	CABRERA	234
C0048	CABRERA	234
C0049	CABRERA	234
C0050	CABRERA	234
C0071	FORMENTERA	230
C0072	FORMENTERA	230
C0073	FORMENTERA	230
C0074	FORMENTERA	230
C0075	FORMENTERA	231
C0076	FORMENTERA	231
C0077	FORMENTERA	231
C0078	FORMENTERA	231
C0079	FORMENTERA	231
C0080	FORMENTERA	231
C0081	CIES	256
C0082	CIES	256
C0083	METACRILATO	254
C0084	METACRILATO	254
C0085	COLUMBRETES	195
C0086	COLUMBRETES	195
C0087	COLUMBRETES	194
C0089	TAHITI	96
C0101	BORA BORA	88
C0102	BORA BORA	88

C0103	BORA BORA	92
C0104	BORA BORA	92
C0111	BORA BORA	88
C0112	BORA BORA	88
C0113	BORA BORA	92
C0114	BORA BORA	92
C0115	BORA BORA	92
C0116	BORA BORA	92
C0117	BORA BORA	90
C0118	BORA BORA	90
C0119	BORA BORA	88
C0120	BORA BORA	88
C0124	BORA BORA	90
C0125	BORA BORA	90
C0126	BORA BORA	90
C0127	BORA BORA	88
C0128	BORA BORA	88
C0129	BORA BORA	90
C0130	BORA BORA	90
C0131	BORA BORA	88
C0132	BORA BORA	88
C0133	BORA BORA	90
C0134	BORA BORA	90
C0160	COMFORT GU10	248
C0161	COMFORT GU10	248
C0162	COMFORT GU10	248
C0163	COMFORT GU10	248
C0164	COMFORT GU10	248
C0165	COMFORT GU10	248
C0180	SAONA	238
C0181	SAONA	238
C0182	SAONA	239
C0183	SAONA	239
C0184	SAONA	238
C0185	SAONA	238
C0186	SAONA	239
C0187	SAONA	239
C0190	SAONA	240
C0191	SAONA	240
C0192	SAONA	241

C0193	SAONA	241
C0194	SAONA	240
C0195	SAONA	240
C0196	SAONA	241
C0197	SAONA	241
R09114	BOMBILLA BULB E14	452
R09115	BOMBILLA BULB E14	451
R09116	BOMBILLA BULB E14	452
R09117	BOMBILLA BULB E14	453
R09118	BOMBILLA BULB E14	453
R09122	BOMBILLA BULB E27	459
R09123	BOMBILLA BULB E27	459
R09131	BOMBILLA BULB E27	456
R09132	BOMBILLA BULB E27	456
R09133	BOMBILLA BULB E27	455
R09134	BOMBILLA BULB E27	455
R09135	BOMBILLA BULB E27	457
R09136	BOMBILLA BULB E27	457
R09137	BOMBILLA BULB E27	458
R09139	BOMBILLA BULB E27	458
R09140	BOMBILLA BULB E27	458
R09156	BOMBILLA BULB GU10	448
R09157	BOMBILLA BULB GU10	448
R09158	BOMBILLA BULB GU10	448
R09159	BOMBILLA BULB GU10	448
R09182	BOMBILLA BULB G9	445
R09184	BOMBILLA BULB G9	444
R09185	BOMBILLA BULB G9	444
R09194	BOMBILLA BULB GU10	449
R09195	BOMBILLA BULB GU10	449
R09196	BOMBILLA BULB GU10	449
R09197	BOMBILLA BULB GU10	449
R09202	BOMBILLA BULB G9	445
R09203	BOMBILLA BULB G9	445
R09204	BOMBILLA BULB E27	463
R09205	BOMBILLA BULB E27	463
R09206	BOMBILLA BULB E27	462
R09207	BOMBILLA BULB GU10	447

R09208	BOMBILLA BULB E14	451
R09209	BOMBILLA BULB G4	446
R09210	BOMBILLA BULB G4	446
R09211	BOMBILLA BULB E27	456
R09212	BOMBILLA BULB E27	459
R09213	BOMBILLA BULB E27	459
R09214	BOMBILLA BULB GU10	449
R09215	BOMBILLA BULB E27	455
R09218	BOMBILLA BULB GU10	447
R09219	BOMBILLA BULB GU10	447
R09220	BOMBILLA BULB GU10	447
R09221	BOMBILLA BULB E14	453
R09223	BOMBILLA BULB E27	457
R09224	BOMBILLA BULB GX53	465
R09225	BOMBILLA BULB GX53	465
R09226	BOMBILLA BULB G9	444
R09227	BOMBILLA BULB G9	444
R09228	BOMBILLA BULB E27	462
R09229	BOMBILLA BULB E27	461
R09230	BOMBILLA BULB E27	461
R09232	BOMBILLA BULB E27	464
R09233	BOMBILLA BULB E27	464
R09234	BOMBILLA BULB E27	457
R09235	BOMBILLA BULB E27	457
R09237	BOMBILLA BULB E27	454
R09238	BOMBILLA BULB E27	454
R09239	BOMBILLA BULB E14	454
R09240	BOMBILLA BULB E14	454
R09241	BOMBILLA BULB E14	453
R09242	BOMBILLA BULB E14	453
R09243	BOMBILLA BULB G4	446
R09244	BOMBILLA BULB E27	460
R09245	BOMBILLA BULB E27	460
R09246	BOMBILLA BULB E27	460
R09247	BOMBILLA BULB G4	446
R09248	BOMBILLA BULB GX53	465
R09249	BOMBILLA BULB GX53	465
R09250	BOMBILLA BULB E27	456

R09251	BOMBILLA BULB E27	455
R09252	BOMBILLA BULB E27	455
R09253	BOMBILLA BULB E27	455
R09254	BOMBILLA BULB GU10	450
R09255	BOMBILLA BULB GU10	450
R09256	BOMBILLA BULB GU10	450
R09257	BOMBILLA BULB GU10	450
R09258	BOMBILLA BULB GU10	450
R09259	BOMBILLA BULB GU10	450
SKB122	CARRILES TRIFASI-COS TRACKS	219
SKB123	CARRILES TRIFASI-COS TRACKS	219
TU0492	PIQUETA / SPIKE	443
TU0494	BASE SUJECCION / FIXING BASE	443
TU0652	PIQUETA / SPIKE	443
TU0653	PIQUETA / SPIKE	443
TU0662	CONEXIÓN IP68	442
TU0663	CONEXIÓN IP68	442
XTS112	CARRILES TRIFASI-COS TRACKS	219
XTS113	CARRILES TRIFASI-COS TRACKS	219
XTS122	CARRILES TRIFASI-COS TRACKS	219
XTS123	CARRILES TRIFASI-COS TRACKS	219
XTS142	CARRILES TRIFASI-COS TRACKS	220
XTS143	CARRILES TRIFASI-COS TRACKS	220
XTS212	CARRILES TRIFASI-COS TRACKS	220
XTS213	CARRILES TRIFASI-COS TRACKS	220
XTS242	CARRILES TRIFASI-COS TRACKS	220
XTS243	CARRILES TRIFASI-COS TRACKS	220
XTS342	CARRILES TRIFASI-COS TRACKS	220
XTS343	CARRILES TRIFASI-COS TRACKS	220
XTS352	CARRILES TRIFASI-COS TRACKS	220
XTS353	CARRILES TRIFASI-COS TRACKS	220
XTS 362	CARRILES TRIFASI-COS TRACKS	221
XTS 363	CARRILES TRIFASI-COS TRACKS	221
XTS 372	CARRILES TRIFASI-COS TRACKS	221

XTS 373	CARRILES TRIFASI-COS TRACKS	221
XTS 382	CARRILES TRIFASI-COS TRACKS	220
XTS 383	CARRILES TRIFASI-COS TRACKS	220
XTS 392	CARRILES TRIFASI-COS TRACKS	221
XTS 393	CARRILES TRIFASI-COS TRACKS	221
XTS 402	CARRILES TRIFASI-COS TRACKS	221
XTS 403	CARRILES TRIFASI-COS TRACKS	221
XTS41002	CARRILES TRIFASI-COS TRACKS	218
XTS41003	CARRILES TRIFASI-COS TRACKS	218
XTS412	CARRILES TRIFASI-COS TRACKS	219
XTS413	CARRILES TRIFASI-COS TRACKS	219
XTS42002	CARRILES TRIFASI-COS TRACKS	218
XTS42003	CARRILES TRIFASI-COS TRACKS	218
XTSF102	CARRILES TRIFASI-COS TRACKS	219
XTSF103	CARRILES TRIFASI-COS TRACKS	219
XTSF302	CARRILES TRIFASI-COS TRACKS	219
XTSF303	CARRILES TRIFASI-COS TRACKS	219
XTSF41002	CARRILES TRIFASI-COS TRACKS	218
XTSF41003	CARRILES TRIFASI-COS TRACKS	218
XTSF42002	CARRILES TRIFASI-COS TRACKS	218
XTSF42003	CARRILES TRIFASI-COS TRACKS	218



## Créditos

### Dirección de arte

Vicente Moya

José Ignacio Ballester

### Fotografías 3D

Javier Gilabert Photographer

Vicente Moreno

Cualiti Photo Studio

Sergi Penalba

Estudios Aviñó

### Diseño gráfico y Comunicación

Amparo Navarro

creativo@mantraco.org

### MANTRA

Pol. Ind. Los Vientos

Calle Alisio, parcela nº4

46119 Náquera · Valencia · Spain

Tel. +34 96 160 99 50

mantra@mantraco.org

### Depto. Nacional

Tel. +34 96 160 99 50

mar@mantraco.org

### Depto. Internacional

Tel. +34 96 160 99 50

c.ando@mantraco.org

© copyright - Global Manufacturing and trading company S.L



Himalaya

Santiago Sevillano Studio



watch MANTRA videos

